
Subject Index

- Activation energy, 26
Activation volume, 25
Aluminosilicate glass, 28
Aluminum oxide, 41, 143, 219
 fracture energy of, 151, 161
 quenching of, 139
Anisotropy, 111, 152, 169, 177, 193, 213
Applied moment DCB, 40, 41
Area
 fracture surface, 212
 of loading curve, 58
 slit island, 195, 197
 stressed, 8, 116, 127, 155, 156, 160
ASTM Standards
 C1161-13, 119
 C1211-18, 119
 C1239-07, 110, 113, 119, 191
 C1273-15, 119
 C1322-96a, 177
 C1323-16, 95, 98, 119
 C1368-06, 228
 C1421-01b, 53
 C1499-01, 80–82, 84, 96, 97,
 120, 165
 C1525-04, 135
 C1684-18, 119
Atomic
 AFM, 54, 111, 125, 128
 bonds, 8, 12, 128
 dimension, 8, 125, 128
 force microscope, 179, 195
 orbitals, 30
Ball-on-ring test, 84, 87, 165
Ball-on-three-balls test, 84, 89
Barium titanate, 3, 217
Biaxial flexure tests, 80, 84, 85, 105,
 106, 120, 124
Biaxial stress, 86, 100, 122
BioloX, 3
Biomaterials, 5, 103–105, 168
Biot number, 132
Bond energy, 150
Borosilicate glass, 28
Branching angle, 189, 190
Brazilian disk test, 100
Brittle fracture, failure, 3–8, 108, 160,
 170, 223, 229
Brittleness, 1, 2, 81, 168
Ceramics, 1–4, 32, 38, 40, 44, 207,
 213–215, 218, 219
Chemical reaction rate theory, 26
Chevron notch bend test, 53–55
Circumferential tension, 87, 97–99, 123
Cleavage, 146
Compliance, 13, 87
Compression, 96–98, 100–103, 163

The Fracture of Brittle Materials: Testing and Analysis, Second Edition.

Stephen W. Freiman and John J. Mecholsky, Jr.

© 2019 The American Ceramic Society. Published 2019 by John Wiley & Sons, Inc.

- Compressive strength, 103
- Contoured DCB specimen, 42
- Coplanar maximum strain energy
 - release-rate criterion, 15
- Coverage, 116–118
- Crack branching, 171–173, 193, 198, 200
- Crack bridging, 212, 218, 219
- Crack extension, 24, 58, 68, 210, 217
- Crack growth rate, 26–35, 45, 49, 145
- Crack growth threshold, 29
- Crack tip, 1, 7, 9–12, 16, 17, 26–35, 39, 40, 45, 176, 191
 - process zone at, 215–218
- C ring specimen, 95–98, 110–112, 121
- Critical stress intensity factor, 12, 64, 100, 127, 130, 146

- DCDC Specimen, 59
- Defect(s), 2, 4, 7, 19, 32, 72, 90, 207
- Delayed failure, 23–25, 116–118
- Density functional theory, 152
- Dental materials, 1, 2, 104, 188
- Diametral compression test, 62, 63, 100, 101
- Double cantilever beam specimen, 38–49
 - applied moment, 40–45
 - contoured, 42
 - wedge loaded, 43
- Double cleavage drilled compression specimen, 53, 54
- Double torsion specimen, 47, 57, 73
- Dynamic fatigue, 228

- Edge chipping, 66–68
- Elastic modulus, 9, 146, 147, 149, 215, 216
- Elliptical integral, 12
- Environmentally enhanced crack
 - growth, 13, 23–36, 54, 65, 223, 225, 226, 232
- Equibiaxial strength, 84
- Error propagation, 231, 232

- Failure criterion, 148
- Failure probability, 111, 112
- Fiber tests, 94, 95
- Finishing operation, 2, 102, 151
- Finite element analysis, 12, 94, 98, 102–105
- Flaws, 3, 8, 17, 79, 113, 114, 122, 207–211, 219
- Flexural testing
 - biaxial, 80, 84, 85, 105, 106, 120, 124, 225, 231
 - 2-point bend, 95
 - 3-point flexure, 50, 80, 82, 105, 113, 121, 134, 142
 - 4-point flexure, 80, 82, 83, 119, 130
 - uniaxial, 80, 225, 231
- Fractal analysis
 - dimensions, 156, 159, 194, 195, 197–199
 - geometry, 156, 197
- Fractography, fractographic analysis, 5, 51, 83, 89, 94, 106, 107, 109, 111–114, 118, 122, 123, 128, 129, 152, 159, 167–169, 171, 175, 177–190
- Fracture
 - atomistics of, 162
 - fast, 82
 - indentation, 60, 61
 - mirror, 15, 82, 101, 109, 111–120, 125, 128–130, 159, 167–170
 - mixed mode, 9, 13–17, 60–64
 - slow, 19–31
- Fracture energy, 9, 12, 14, 146, 149, 151, 210
- Fracture mechanics, 10, 15, 20, 32, 52, 60, 65, 66, 99, 100, 127–129, 134

- Fracture surface, 8, 10, 15, 27, 51, 105, 158
- Fracture toughness, 12–14, 17, 37–74
- Gallium arsenide, 2
- Generalized maximum tangential stress criterion, 18, 19
- Glass, 2, 7, 8, 23–35, 42, 45, 49, 56, 64–67, 84
- Glass fibers, 2, 8
- Goodness of fit, 229
- Grains, 207–220
- Griffith theory, 7, 8, 12–18
- Groove, grooving, 39, 42, 44, 45, 47, 55, 73
- Hackle, 170–172, 177, 179, 187, 189–195, 200, 201, 237
- Hardness, 2, 61, 62, 64, 66, 68
- Hardness impression, 55, 60, 61
- Hartree Fock model, 154
- High temperature testing, 61, 92, 93, 100
- Hourglass specimens, 104, 105
- Indentation cracks, 68, 90, 112, 114, 121, 163
- Indentation fracture technique, 60–62
- Intrinsic origins, 169
- ISO Standards, 48–50
- ISO, 14704:2016 (flexural strength, RT), 120
- ISO, 15490:2008 (tensile strength, RT), 120
- ISO, 15732:2003 (flexural strength, SEPB), 56
- ISO, 6872 (Dental Ceramics), 89, 110
- ISO, 17565:2003 (flexural strength, HT), 120
- ISO, 18756:2003 (flexural strength, SCF), 56
- ISO, 23146:2008 (flexural Strength, SEVNB), 56
- ISO, 24370 (fracture toughness, CNB), 54
- K_{Bj} , 16, 104, 113, 116
- K_{IC} , 11–14, 32, 34, 36, 39, 40, 43, 45, 48–51, 55–57, 65, 66, 209, 219
- Kinks in crack, 155
- Knoop indentation, 49
- Laminate testing, 105–108
- Lattice trapping, 152
- Lifetime prediction, 237
- Loading modes, 10
- Lower confidence bound, 116
- Lower prediction bound, 116
- Lower tolerance limit, 225, 229
- Machining, 2, 16, 17, 43, 52, 53, 83, 90, 92–95, 112–114
- Maximum normal stress criterion, 14, 16
- Maximum strain energy release-rate criterion, 14, 16, 64
- Mechanisms of crack growth, 30–35
- MEMS devices, 101
- Metallic glasses, 150
- Microcracking, 213–217
- Military handbook, 177
- Mirror, 15, 94, 170–199
- Mirror-to-crack size ratio, 117, 128
- Mist, 15, 170–200
- Mixed mode, 14–19, 68–72, 101, 109, 119, 135, 136, 211
- Molecular dynamics calculations, 155, 160
- Molecular orbital calculations, 153
- NIST Recommended Practice Guide, 109, 119, 177, 187, 190
- Non-coplanar maximum strain energy release-rate criterion, 14
- Nondestructive evaluation, 224

- Optical fiber, 102, 105, 166, 168, 169
- O ring test, 95–99, 110–112
- Partial pressure of water, 12, 27
- pH, 27
- Phase transformation(s), 213, 215, 217
- Plane strain, 12–14, 42, 100, 163, 169
- Plane stress, 12, 13, 100
- Plastic deformation, 7
- Polycrystalline, 39–41, 45, 65, 66, 95, 119, 120, 127, 209, 210, 212, 215, 219
- Pores, 169
- Probability of failure, 91–95, 122, 123, 148, 155, 190, 191
- Process zone, 216
- Proof test, 94, 223, 224
- Quartz, fracture energy of, 151
- Quenching, 135
- Radial cracks, 60, 163
- R-curve, 215, 217–219
- Regions of crack growth, 25, 28, 29, 32, 116
- Relative humidity, 12, 45
- Reliability, 2, 4, 5, 223, 225–227, 229
- Residual stress
 - global, 129
 - local, 129, 137, 150, 169, 182
- Retained strength, 140
- Ring testing
 - ball-on-ring test, 84, 87, 165
 - piston-on-ring test, 84, 85, 89
 - ring-on-ring, 84–87, 114, 225
 - rings in flexure, 95
- Scaling, 194, 195, 198
- Silica, 28, 144, 154, 159, 161
- Silicon, 2, 152, 154, 161
- Silicon carbide, 2, 94, 146, 151, 227
- Silicon nitride, 2, 3, 227
- Single edge notched beam test, 53
- Single edge pre-cracked beam test, 55
- Slow crack growth, 13, 16, 61, 99, 113, 116, 117, 129, 130, 135, 142, 148, 151, 156, 159, 160, 164, 165, 171
- Soda-lime-silica glass, 24, 26, 27, 95, 108, 113, 116–118, 121, 125, 149, 188, 192
- Sources of failure, 71, 94, 101
- Stable crack growth, 50, 57, 62, 82, 142
- Static fatigue, 19, 23
- Statistics of fracture, 108–113, 156, 223, 229
- Strain energy release rate, 10, 15, 17, 18
- Strength
 - strength, indentation, 61
 - strength distribution, 109–115, 122, 223, 225, 231
- Stress corrosion, 25
- Stress distribution, 83, 87, 89, 90, 98, 104
- Stress intensity factor, 11, 24–35, 37, 48, 54, 57, 60, 62, 71, 72, 134, 191, 193, 197, 211, 216
- Subcritical crack growth, 11, 13, 63, 157, 162, 164, 171
- Surface crack, 11–14, 52, 56, 64, 80, 109
- Surface crack in flexure test, 56
- Tapered DCB specimen, 42
- Tensile tests, 79, 90–95, 104, 114, 152
- Thermal expansion anisotropy, 101, 213
- Thermal shock, 5, 130
- Thermal shock tests, 135–141
- Thermal stress, 130–133
- Theta specimen, 101, 102, 120
- Time to failure, 116
- Tolerance limit, 155, 156
- Toughening, 207, 212, 213, 215–217, 219
- Toughness tests
 - chevron notch bend test, 48, 49

- double cantilever beam, 32–38
- double cleavage drilled compression (DCDC), 53, 54
- double torsion, 40–43
- single edge notched beam, 47
- single edge pre-cracked beam, 49, 50
- Tractions, 217
- Transducers, 1
- Tubular components, 98–100, 110
- Twist hackle, 177, 179, 187, 191–193

- Uncertainty calculations, 109, 113, 115, 116, 118
- Uniaxial tension, 92, 94, 119
- Universal Binding Energy Relation (UBER), 151

- Variance, 229, 231
- Vickers hardness indentation, 39, 49, 50, 55, 60, 61, 164
- Vitreous silica, 29, 33
- Volume defects, 17, 102, 103

- Wake hackle, 187, 189
- Wallner lines, 187, 188, 190
- Wedge loaded DCB specimen, 38, 39
- Weibull distribution, 109–116, 153–156, 229
- Work of fracture test, 58

- Zinc Selenide (ZnSe), 177, 179
- Zinc Sulfide (ZnS), 161
- Zirconia (ZrO_2), 57, 107, 120, 141, 143

