

## Index

### a

*ab initio* molecular dynamics (AIMD) 479, 480  
*ab initio* wavefunction methods 476–477  
 accelerated molecular dynamics (aMD) 486  
 acrylonitrilebutadiene-styrene resins 403  
 additive technology 500  
 adiabatic flow  
   stagnation pressure 149  
   two-phase gas-liquid flow 170–171  
 adiabatic model 134–137  
 adiponitrile 403  
 adsorption isotherm 91–94  
 Advanced Research Project Agency–Energy (ARPA–E) 471  
 air contaminants 305  
 Air Products (AP-X™) 242  
 Algorithm for continuous/integer global optimization of nonlinear equations (ANTIGONE) 208  
 alternative fracturing fluids  
   broader economic and environmental benefits 47  
   cost of 33, 41–42  
   CO<sub>2</sub> vs. LPG 43–45  
   environmental and microeconomic impacts 47–49  
   flowback and recycling 45–46  
   improved operations with 39–47  
   saltwater disposal sites, availability of 42–43  
   seismic implications 46  
   unlocking arid and water sensitive shales 46–47  
 American Industrial Hygiene Association (AIHA) 305  
 American Society for Testing and Materials (ASTM)  
   D975 requirements 415  
   D1655 specification 527, 528–529, 534, 535, 539, 540  
   D7566 specification 414, 527, 528  
 amine sweetening 184  
 Anderson-Schulz-Flory (ASF) distribution 271–272, 440, 441

annualized fixed cost 225  
 Anton Paar DMA 4100, 419, 422  
 Anton Paar SVM3000 based on ASTM D-7042 419, 423  
 aqueous dew point temperature 341  
 Aroforming process 384  
 aromatization of light alkanes. *see* light alkane aromatization  
 As-Low-As-Reasonably-Practicable (ALARP) 311  
 ASPEN Plus  
   flowsheet 268–273  
   process 406, 445, 446  
 atmospheric distillation analysis 419–421  
 atoms-in-molecules (AIM) analysis 467  
 auto-ignition temperature (AIT) 326, 327  
 auto thermal reforming (ATR) 271, 272, 439, 440

### b

balance of plant (BOF) 511, 523  
 Barnett shale 22  
 Bernoulli's equation  
   compressible pipeline flow 133  
   flow between vessels 150  
   fluid mechanics 123–124  
   rationalization with 138–139  
 Berthelot-Lorentz combining rules 62  
 beta-type zeolites 393  
 bi-fuel/dual fuel 23  
 billion standard cubic feet per day (BSCFD) 499  
 binary interaction parameters (BIP) 60, 348–350  
 binary systems of NG components with water 347–351  
 biofuels 505–507  
 blending/pooling problems 199  
 boiling liquid expanding vapor explosion (BLEVE) 320, 326  
 boiling water reactors (BWR) 289  
 bond critical points (BCP) 467  
 Brønsted acid sites (BAS) 383, 393–394

bubble-point curve 59  
 Bukacek's method 342  
 butadiene  
   petrochemical industry 403  
   process description 404–405  
   production capacity of 403  
   steam cracking 403  
   techno-economic analysis 406–410  
 Butler Volmer reaction mechanism 515  
 Byogy renewables process 506–508  
  
**C**  
 capital investment 23, 37–38  
 carbon dioxide fracturing 25–26  
 carbon number distribution 435, 436  
 carbon sequestration 34  
 catalytic steam reforming 509  
 C9–C14 cut 437  
 Cetane Index Calculation 426–427  
 Cetane number (CN) 427  
 C7+ fraction characterization 65, 70  
 Chabazite-type zeolite 393  
 chemical conversion routes 10  
 chemical production complex 230  
 Chevron Phillips' Aromax process 384  
 chloroprene 403  
 choked flow  
   compressible pipeline flow 137–138  
   critical pressure ratio 157  
   maximum flow rate 157–158  
   meters 156–158  
   problem 158–159  
 circulating fluidized bed reactor 441  
 coalbed characteristics 89–91  
 coalbed methane (CBM) 4, 90  
 coal composition 90  
 coal formation  
   adsorption isotherm 91–94  
   coal wettability 95–100  
   enhanced coalbed methane (ECBM) process  
     89–90, 95, 101–103, 106  
   gas storage in 91, 92  
   pilot field tests 106–107  
   properties and the operation 108  
   Young's modulus and Poisson's ratio 105  
 coal salinity 90  
 coal softening 105–106  
 coal-to-liquid (CTL) technology 439  
 coal-water–air systems 95, 96  
 coal wettability 95–100  
 coarse-grained molecular dynamics (CGMD)  
   486

CO<sub>2</sub> emissions  
   and energy demand 16  
   environmental assessment 266  
   reduction 60, 81, 379, 466  
 CO<sub>2</sub> injectivity 89, 101–106, 108  
 cold filter plugging point (CFPP) 435  
 Colebrook-White equation 127, 128, 165  
 combined heat and power (CHP) 511–512  
 combined reforming of methane (CRM) 440  
 combining rule 1 (CR-1) 345  
 complete active space self-consistent field (CASSCF)  
   478  
 compressible pipeline flow  
   adiabatic model 134–137  
   application 139  
   Bernoulli approximation 133  
   choked flow 137–138  
   control valve 159–160  
   flow between vessels 150–151  
   isentropic flow 133–134  
   isothermal flow 132–133  
   meters 153–155  
   polytropic flow 134  
   rationalization with Bernoulli's equation  
     138–139  
   stagnation pressure for 148  
 compression performance model 207–208,  
   217–218  
 compressor/pump stations 180  
 computational fluid dynamics (CFD) models 325  
 computer-aided process engineering (CAPE) 76  
 Co nanoparticles 466, 467  
 contact angle 95–100  
 continuity equation 121–122  
 continuous catalyst regeneration (CCR) technology  
   382  
 Control of Industrial Major Accident Hazards  
   (CIMAH) regulations 332  
 control valve  
   compressible flow 159–160  
   incompressible flow 159  
   problem 161  
 conventional diesel fuels 414  
 conventional FT reactors 441  
 conventional GTL plant setup 452  
 CO<sub>2</sub> removal 17, 267, 282  
 CO<sub>2</sub> sequestration 89  
   and capture 47  
   environmental improvements 34  
   hydraulic fracturing 45  
   process 95

Crane Handbook 139–142  
 cricondenbar pressure (cricoP) 58, 59  
 cricondentherm temperature (cricoT) 59  
 criteria air pollutants (CAP) 222  
 critical point 59, 165, 176  
 critical pressure ratio 157  
 CSMGem 469  
 cubic equations of state (EoS) 59  
   effect of characterization 65  
 Cubic-Plus-Association equation of state (CPA)  
   344–346  
 CYCLAR process 384–385, 395

## d

Darcy friction factor 124, 126, 127  
 decline stage, CBM 90  
 degrees of freedom 171, 479, 486  
 demethanizer pressure 241, 251–254  
 density functional theory (DFT) 470, 478  
 dewatering 17, 90  
 dew-point curve (CBDE) 59  
 dew point temperatures 341–342  
 diesel fractionation 420, 421  
 di-ethylene glycol (DEG) 368  
 direct internal reforming (DIR) SOFC  
   closed-loop validation results 523  
   energy balance 514  
   power demand 517  
   schematic diagram of 513  
 discharge coefficient 153–156  
 dispersion models 324  
 dissipative particle dynamics (DPD) 486  
 distributed energy production 511–512  
 Domino effects 321  
 Dow Fire & Explosion Index 231–232  
 down hole PVT 175–176  
 drilling rigs 27  
 dry reforming of methane (DRM) process 440  
 dual fuel systems  
   conversion to 31–32  
   environmental remediation 23  
 dual mixed refrigerant (DMR) 242  
 Dukler and Taitel method 162–164  
 dynamic viscosity 131

## e

Elliott combining rule (ECR) 345  
 Emergency Response and Guidelines (ERPGs) 305  
 end users 206, 217  
 energy balance 132  
 energy gain 128

energy loss 128  
 energy needs 60  
 Energy-related Severe Accident Database (ENSAD)  
   306  
 enhanced coalbed methane (ECBM) process 89–90,  
   95, 101–103, 106  
 enthalpy 119  
 environmental remediation  
   emissions factors 32  
   of GHG  
     bi-fuel/dual fuel 23  
     environmental impact 24  
     forms 23–24  
     single fuel 23  
   improved operations with  
     broader economic 38–39  
     capital investment analysis 37–38  
     and environmental benefits 38–39  
   water and seismic impacts  
     recycling produced water 26–27  
     waterless fracturing 24–26  
 EPCON Process Innovator® 113, 129, 139, 143  
 EPCON's CHEMPRO 152  
 equation of state (EoS) 59  
   process simulator 176  
   thermodynamics of fluids 120–121  
 equilibrium constant 96  
 ethane recovery 251–254  
 ethylene-to-butadiene portion 404, 405  
 Eulerian-Lagrangian spray model 331

## f

Fanning friction factor 123  
 fault tree analysis (FTA) 314  
 first law of thermodynamics 117–118  
 Fischer-Tropsch synthesis (FTS) 11, 263–264, 413,  
   505  
   ASF distribution model 440, 441  
   cobalt-based catalyst 440  
   conventional FT reactors 441  
   iron-based catalyst 440  
   jet fuel 527  
   kinetics 480–481  
   larger size and time scales molecular simulation  
     481–485  
   LTFT and HTFT process 441  
   physical and morphological properties of 466  
   SCF (*see* supercritical fluids (SCF) in FT synthesis)  
   supercritical fluids in 442  
   vs. Synfuels product distribution 502, 503  
   syngas conversion to hydrocarbons 478

- fixed capital investment 226
  - fixed fluidized bed reactor 441
  - flash point analysis 420, 425
  - flow between vessels
    - compressible flow 150–151
    - incompressible flow 150
  - flow coefficient 159
  - flow nozzle 155–156
  - fluid flow
    - compressible pipeline flow 132–139
    - control valves 159–161
    - Crane Handbook 139–142
    - fundamental equations of fluid mechanics 121–126
    - incompressible pipeline flow 126–129
    - laminar flow 130–132
    - meters 152–159
    - notation 143–145
    - pipng networks 145–152
    - thermodynamics of fluids 116–121
    - two-phase gas-liquid flow 161–171
    - units of measure 114–116
  - fluid mechanics
    - Bernoulli's equation 123–124
    - continuity equation 121–122
    - mechanical energy balance 124–125
    - momentum balance 122–123
    - speed of sound 125–126
    - total energy balance 125
  - fluid velocity 146
  - fouling factor 128
  - fracture propagation 21
  - fresh water
    - consumption 20
    - management 29
  - friction factor 127
  - FTS. *see* Fischer-Tropsch synthesis (FTS)
  - fuel prices 30
  - fuel usage
    - annual and costs 30
    - transport vehicle 29
    - by well 28–30
- g**
- gallium 387–388
  - GasCalc software 344, 357
  - gas chromatograph (GC) 419
  - gas condensate
    - real gas condensate (RGC) mixtures 72–75
    - synthetic gas condensates 71–72
  - gas expansion coefficient 154
  - gas fracturing 25, 44
  - gas hydrates 467–470
  - gas storage, in coal formation 91, 92
  - gas subcooled process (GSP) 236
  - gas sweetening 465
  - gas-to-liquids (GTL) 11
    - ASTM specifications 415
    - best model tested 435–437
    - carbon number distribution 435, 436
    - composition-property prediction models
      - calibrating model method 428, 429
      - empirical model method 428–431
      - model testing 428
      - regression analysis 427–428
    - conventional diesel fuels 414–415
    - diesel specifications 415, 416
    - diesel splitter downstream 436
    - experimental study
      - aim of 416–417
      - atmospheric distillation analysis 419–421
      - carbon distribution 419, 422
      - Cetane Index Calculation 426–427
      - cloud and pour points analysis 420, 425–426
      - density analysis 419, 422–424
      - diesel fractionation 420, 421
      - distillation 418–419
      - flash point analysis 420, 425
      - methodology 417
      - and modeling study 417
      - standard testing methods 417, 418
      - viscosity analysis 419, 423–424
  - FT process 413
  - FTS 440–442
    - kinetics 480–481
    - larger size and time scales molecular simulation 481–485
    - and morphological properties 466
    - physical properties 466
  - GTL process 465–466
  - hydrate formers 465
  - hydrocarbon combination 414
  - KMC 480–481
  - new specification formulation 435
  - process simulation 263–264, 271–272
  - products upgrading 442–444
  - quantum level investigations
    - methane conversion to syngas 477–478
    - methods and models 476–477
    - solvation effects 479–480
    - syngas conversion to hydrocarbons 478–479
  - standard error 435

syngas 439–440, 466  
 ULSD 414  
 gas to oil ratio (GOR) 175  
 gas turbines 509  
 Gaussian model 325  
 general AMBER force field (GAFF) 473  
 generalized gradient approximation (GGA) 478  
 GERG-water  
   correlation 342  
   EoS 343–344  
   pure component parameters 347–348  
 Gibbs energy ( $G^E$ ) 64  
 Gibbs ensemble MC simulations 470  
 Gibbs phase rule 171  
 global energy sources 2  
 glycol dehydration 76, 189–190  
 gPROMS<sup>®</sup> 517  
 grand canonical ensemble 481  
 grand canonical Monte Carlo (GCMC) simulations  
   347, 470, 474  
 gravimetric energy density 510, 511  
 greedy coverage algorithm 330  
 greenhouse gases (GHG) 198, 222, 509–510  
   factors 31  
   from fuel burn 30–31  
   improved operations  
     broader economic 38–39  
     capital investment analysis 37–38  
     and environmental benefits 38–39  
   shale gas wells 31–32  
 grouped carbon number model 417, 432–436  
 GTL fuels. *see* gas-to-liquids (GTL)

## h

Hartree-Fock (HF) formalism 477  
 heat capacity 118–119  
 heat exchange reforming 439, 440  
 heavy ends recovered (HER) 450  
 heavy oils 500  
 high-temperature Fischer-Tropsch (HTFT) 289,  
   441  
 high-volatile A bitumen (hvAb) 95  
 high-volatile B bitumen (hvBb) 95  
 hockey stick 22  
 homogeneous flow model 165–166  
 Honeywell's UniSim<sup>®</sup> 76  
 horizontal gas-liquid flow 162  
 Houdry process 403  
 HYDRAFLASH software 372  
 hydrate formers 465  
 hydrate point temperature 342  
 hydraulic fracturing 16–17  
   completions phase 19, 23  
   drilling phase 19, 23  
   flowback/recovery of 33–34  
   fresh water consumption 20  
   impacts 31  
   operations after environmental remediation of  
     32–34  
   production phase 19, 23  
   quality of water produced 27  
   and seismicity 18  
   shale gas operations 19–20  
   transportation and disposal of produced water 20  
   and water impacts 19–20  
 hydrocarbon compounds 70  
 hydrocarbon dew point (HCDP) 59  
 hydrocarbon liquid dropout 59  
 hydrocarbon mixture, PT phase diagram 58  
 hydrocarbon process simulation 173–174  
 hydrogenation reactor 504

## i

ice formation 341  
 ideal gas law 119  
 incinerator/flare 189  
 incipient wetness impregnation (IWI) 386  
 incompressible pipeline flow  
   application 129  
   control valve 159  
   flow between vessels 150  
   fouling factor 128  
   friction factor 127  
   K-factors for fittings 127  
   meters 152–153  
   other head loss and gain terms 128–129  
   Reynolds number 126  
   stagnation pressure 146–147  
 indirect internal reforming (IIR) 512  
 induced seismicity 21  
 initial boiling points (IBP) 418, 419  
 internal combustion engines (ICE) 509  
 internal reforming solid oxide fuel cell (IR SOFC)  
   512  
 International Electro-Technical Commission (IEC)  
   316  
 intrinsic rate of potential energy 222  
 isentropic exponent 119  
 isentropic flow  
   compressible pipeline flow 133–134  
   process 126  
   rationalization with Bernoulli's equation 138

isentropic flow (*contd.*)  
 stagnation pressure 148–149  
 two-phase gas-liquid flow 168–170  
 isoquality lines 58, 59  
 isothermal flow  
 compressible pipeline flow 132–133  
 rationalization with Bernoulli's equation 138  
 stagnation pressure 147–148  
 two-phase gas-liquid flow 167–168

## j

jet fuel 503, 527. *see also* synthetic jet fuel  
 Joule's constant 114  
 Joule–Thomson (J–T) effect 237, 241–242

## k

Kaiser Wilhelm Institute for Coal Research (KWI) 440  
 Kalman filter 520  
 kerogens porosity 472–476  
 K-factors for fittings 127, 150  
 Kihara potential 346, 373, 374  
 kinematic viscosity 415, 416, 418, 419, 423, 424, 431, 435, 436  
 kinetic Monte Carlo (KMC) methods 471, 480–481

## l

Langmuir adsorption constant 346  
 Langmuir Hinshelwood kinetics 515  
 Langmuir pressure 103  
 Langmuir-type mathematical expressions 347  
 Layer of Protection Analysis (LOPA) 311  
 Le Chatelier equation 326  
 Lennard-Jones (LJ) dummy particle 472, 474  
 Lewis acid sites (LAS) 393–394  
 light alkane aromatization  
 acidity/Si/Al ratio 393–394  
 metals role  
 bifunctional mechanism 385, 386  
 Ga/H-ZSM-5 387–388  
 Mo/ZSM-5 386  
 promoters 391–392  
 Pt/H-ZSM-5 387  
 Re/H-ZSM-5 388–389  
 Zn/H-ZSM-5 389–391  
 natural gas composition 380–381  
 pore structure  
 ZSM-5 392  
 ZSM-8 393  
 ZSM-11 393  
 ZSM-12 393  
 shale gas revolution 379

thermodynamics and history 381–383  
 light GTL diesel cut 423, 437  
 limiting pore diameter (LPD) 473–474  
 linear alkyl benzene (LAB) 422, 437  
 Linear Combination Vidal Michelsen (LCVM) 60  
 linear programming (LP) model  
 case study 279–280  
 formulation 278  
 steady-state simulation 278  
 LINGO<sup>®</sup> 221, 229, 277, 279, 287, 295, 418, 428, 429, 431, 433  
 liquefaction process analysis 244  
 liquefied petroleum gas fracturing 25  
 liquid–liquid equilibrium (LLE) 483  
 liquid-phase hydrogenation 501  
 LNG process simulation 266–271  
 lower flammability limit (LFL) 326  
 low-temperature Fischer-Tropsch (LTFT) 289, 441, 466

## m

Mach number 135, 136, 138, 147, 168  
 Markov method 314  
 Master equation (ME) 480  
 Mathias-Copeman parameters 64, 356  
 MATLAB 521  
 maximum covering location problem (MCLP) 330, 331  
 maximum flow rate 157–158  
 maximum water precipitation temperature 342  
 mean time between failure (MTBF)/mean time between failure (MTBF) 313  
 mechanical energy balance 124–125  
 membrane distillation 27  
 meters  
 choked flow through 156–158  
 compressible flow through 153–155  
 flow nozzle 155–156  
 incompressible flow through 152–153  
 orifice meter 155  
 problem 158–159  
 Venturi tube 156  
 methane 511  
 methane adsorption isotherm 92  
 methanol/ethylene glycol injection 180–182  
 methanol process simulation 272–274  
 methanol synthesis reactors 289  
 MFI zeolite 392  
 M-2 forming process 384  
 midstream sector  
 amine sweetening 184  
 glycol dehydration 189–190

- incinerator/flare 189
  - NGL fractionation 192, 194
  - NGL recovery 190–193
  - processing 464
  - sour water stripper (SWS) 187–189
  - sulfur recovery unit (SRU) 184–186
  - tail gas treatment unit (TGTU) 186–187
  - million metric ton per annum (MMTA) 221, 229
  - minimal cut-sets 314
  - minimum source distance problem (MSDP) 330
  - mixed fluid cascade (MFC) 242
  - mixed-integer nonlinear programming (MINLP) 197, 221
    - case study 286–288, 293–296
    - formulation 285–286, 290–293
    - problem statement and solution strategy 284–285
    - process descriptions 282–284
  - mixed refrigerant cycles (MRC) 242
  - mixing stations 205–206, 216–217
  - molecular dynamics (MD) simulations 465
  - molecular mechanics (MM) 479
  - molecular simulations 465
  - Moller–Plesset second order perturbation theory (MP2) 477
  - molybdenum 386
  - momentum balance 122–123
  - monetization routes
    - advantages and disadvantages for 6–9
    - chain with different routes 10
    - export 7–9
    - large industries and power plants 4–6
    - residential 7
    - small/medium industries and commercial users 6–7
  - Monte Carlo (MC) simulation technique 465
  - mpMPC. *see* multiparametric model predictive control (mpMPC)
  - MSCFD reactor 504
  - MULTIFLASH software 361
  - multifunctional BaZrO<sub>3</sub> membrane 395
  - multifunctional membrane reactor model 395
  - multiparametric model predictive control (mpMPC)
    - controller design 520–522
    - linear model approximation 519–520
  - multiparametric quadratic programming problem (mp-QP) 521
  - multitubular fixed bed reactor 441
- n**
- naphtha 403, 404
  - natural gas
    - bi-fuel/dual fuel 23
    - chain 2–4
    - composition 4, 235, 380–381
    - conventional/unconventional reservoirs 463
    - conversion
      - advantages and constraints in 12
      - to chemicals and fuels 9–13
    - demand of 2
    - electricity generation 509, 510
    - environmental impact 24
    - expansion 11
    - forms 23–24
    - GTL technology
      - FTS kinetics 480–481
      - KMC 480–481
      - quantum level investigations 476–480
    - LNG export 8–9
    - midstream processing of 463, 464
    - molecular simulation techniques 463, 465
    - pipeline export 7–8
    - pipeline transportation 467–470
    - porous media
      - ab initio* DFT 471
      - automotive vehicles 470
      - catalytic processes 470
      - kerogens porosity 472–476
      - molecular modeling 470
      - polymeric membrane technology 471
      - TST 471
    - real natural gas (RG) 67–70
    - role of 6
    - single fuel 23
    - SOFC (*see* solid oxide fuel cell (SOFC))
    - synthetic natural gases (SNGs) 65–67
    - transport and conversion 463, 464
    - transportation fuels 465
    - URR 509
    - value-added chemicals 465
  - natural gas liquids (NGL)
    - energy flow 251
    - ethane extraction 236
    - fractionation
      - midstream sector 192, 194
      - process 235
      - simulation 195
    - methodology framework 237–238
    - optimization
      - framework 238
      - model development 245–249
      - results 249–254
    - propane refrigeration system
      - liquefaction process analysis 244



- natural gas liquids (NGL) (*contd.*)
  - simulation results 244–245
  - recovery
    - compression 244
    - demethanizer 241
    - GSP process for 239
    - Joule–Thomson (J–T) effect 241–242
    - midstream sector 190–193
    - process simulation 195
    - refrigeration 242–244
    - turboexpander 242
  - self-refrigeration cycle 237
- natural gas reformer 439–440
- natural gas reforming 512
- natural gas to acetylene (GTA). *see* Synfuels process
- natural gas to ethylene (GTE). *see* Synfuels process
- natural gas to liquid fuels (GTL). *see* Synfuels process
- net positive suction head (NPHS) 150
- net present value (NPV) 34–35
- network flow 145–146
- network systems
  - blending/pooling problems 199
  - computation study 208–209
  - gas quality in 202–204
  - generic 201
  - inflow qualities 204
  - optimization model 202–208
  - processing and production
    - processing units 282–284
    - proven reserves 261
    - simulation
      - problem statement 265
      - steady state process 266–274
    - superstructure representation 281, 284, 289–290
    - supply chain management 260–261
    - sustainability assessment of 296–300
    - utilization
      - GTL process 263–264
      - LNG process 263
      - methanol process 264–265
    - results 209–212
    - superstructure in Ontario 203
    - supply chains 200–202
- Newton-Raphson algorithm 127
- nitrogen separation/rejection 288
- nonlinear iterative partial least squares (NIPALS)
  - algorithm 531, 532
- nonlinear programming (NLP) model 199
- non-random two-liquid Redlich-Kwong (NRTL-RK)
  - property method 445
- O**
  - offshore process simulation 75–81
  - olefinic C<sub>4</sub> streams 384
  - oligomerization unit 503, 504
  - optimization, for NGL
    - compressor and condenser 249–251
    - demethanizer pressure and ethane recovery 251–254
    - energy balance constraints 247–248
    - heat transfer constraints 247
    - objective function 246
    - pressure ratio constraints 247
    - propane cycle 249
  - optimization model 202–208
  - orifice meter 155
  - overall risk ratings (ORR) 318
  - oxidative coupling of methane 226
- P**
  - parallel mixed refrigerant (PMR) 242
  - PARametric Optimization and Control (PAROC)
    - framework
      - controller design 520–522
      - linear model approximation 519–520
  - partial least squares (PLS) 531–533
  - partial oxidation (POX) 439–440
  - particulate matter (PM) emissions 24
  - PC-SAFT EoS 61–63
  - peak gas stage, CBM 90
  - peak oil 500
  - Peng–Robinson (PR) EoS 59–61, 343
  - pentasil-type zeolite 392
  - Perdew–Wang exchange 478
  - perfect gas properties 119–120
  - perturbed-chain SAFT (PC-SAFT) 61–62
  - Petrotest ADU4+ automatic distillation unit 419
  - phase envelope 58, 179, 181
  - pilot field tests 106–107
  - pipeline modeling 178–180
  - pipeline performance model 207
  - pipeline transportation 467–470
  - piping networks
    - application 151–152
    - flow between vessels 150–151
    - network flow 145–146
    - stagnation pressure 146–149
    - system equations 151
    - total pressure 146–149
  - pitot tube 147
  - platinum(Pt)-based catalysts 387
  - Poiseuille flow 130



- Poisson's ratio 105
  - polybutadiene 403
  - polymer electrolyte membrane (PEMFC) fuel cell 511
  - polymeric membrane technology 471
  - polytropic flow 134, 138
  - potential of mean force (PMF) landscapes 480
  - pressure drop 151, 160
    - characteristics 165
    - entrance effect 164
    - surface tension errors 164
  - pressure-enthalpy flash 171
  - pressure swing adsorption (PSA) 289
  - pressure-temperature (PT) phase diagram 58
  - pressure-volume-temperature (PVT) 175
  - principal component analysis (PCA) 529–531
  - principal components regression (PCR) 531
  - process safety
    - effective mitigation system 329–332
    - equipment and plant reliability 312–315
    - facility siting and layout optimization
      - advances in 318–322
      - lessons learned from past incidents 322–323
      - separation distances 318
    - fire and explosion 326–329
    - incident history
      - Cleveland, Ohio 1944, 306–308
      - Kaohsiung, Taiwan 2014, 309
      - San Bruno, California 2010, 308
      - Skikda, Algeria 2004, 308
    - incidents and evolution 334
    - methods 309–311
    - regulatory program and management systems 332–335
    - relief system design 323–324
    - toxic and heavy gas dispersion 324–325
    - US PSM and RMP regulations 335
  - process simulator
    - defined 174
    - hydrocarbon process simulation 173–174
    - midstream sector 183–192
    - upstream sector 174–183
  - produced water/wastewater
    - fracturing with 26–27
    - recycling (*see* recycling produced water)
    - transportation and disposal of 20
  - ProMax model tracking 177–178, 184, 188–190
  - propane refrigeration system
    - T-H diagram of 249
    - thermodynamic analysis
      - liquefaction process analysis 244
      - simulation results 244–245
- r**
- Rackett model 445
  - radial distribution function (RDF) analysis 472, 484
  - Ras Laffan industrial complex in Qatar 499
  - real gas condensate (RGC) mixtures
    - assigning UNIFAC structure 75
    - dew point predictions 75
    - molar compositions of 74
    - plus fraction characterization of 72–75
    - splitting and lumping 73–74
  - real natural gas (RG)
    - compositions of 69
    - natural gas dew points 67–70
  - ReaxFF potential 481
  - recovery, NGL
    - compression 244
    - demethanizer 241
    - GSP process for 239
    - Joule–Thomson (J–T) effect 241–242
    - midstream sector 190–193
    - process simulation 195
    - refrigeration 242–244
    - turboexpander 242
  - recycling produced water
    - fracturing with produced water 26–27
    - treating wastewater 27
  - refrigeration system
    - liquefaction process analysis 244
    - simulation results 244–245
  - Reid vapor pressure (RVP) 76, 282
  - reserves-to-production (R/P) rates 2
  - residue recycle (RR) 237
  - retrograde region 59
  - reverse MC (RMC) 472
  - Revised Perdew-Burke-Ernzerhof functional (RPBE) 478
  - Reynolds number 126, 155, 165
  - Rhenium 388–389
  - Runge-Kutta-Gill method 171
- s**
- safety instrumented functions (SIF) 311
  - safety relief valve 323
  - saltwater disposal sites 42–43
  - secondary vapor cloud explosions 326
  - second law of thermodynamics 118, 137
  - second order perturbation theory 62

- seismicity
  - and hydraulic fracturing 18
  - impacts 17, 24–27
  - induced 21
  - and seismic implications 21–22, 46
- seismic response 21
- self-refrigeration cycle 237
- separation distances 315, 318, 319
- shale gas extraction 17
- shale gas monetization supply chains
  - case study
    - base case environmental considerations 230–231
    - base case product prices 225
    - base case safety considerations 231–232
    - base case solution 226–227
    - conversion technologies 224–225
    - environmental and safety metrics 222–223
    - feedstock 224
    - objectives of 224
    - plant costs and capacity limits 225–226
    - problem statement 221–222
    - reduced methanol price case results 227–229
    - reduced urea price case results 229–230
  - methodology 220–221
  - optimization formulation 220
  - superstructure representation 220, 221
- shale gas operations
  - completions phase 19
  - drilling phase 19
  - fuel usage 21
  - hydraulic fracturing 19–20
  - seismicity and seismic implications 21–22
  - and water impacts 19–20
- shale gas revolution 379
- shale gas wells
  - Barnett shale 22
  - drilling and production processes 17
  - energy and environmental equation 15–17
  - environmental impacts 17–18
  - environmental remediation
    - of greenhouse gas emissions 31–32
    - of hydraulic fracturing 32–34
    - natural gas as a fuel 22–27
- global energy demand 16
- theoretical calculations
  - annual fuel usage and costs 30
  - conversion to dual fuel systems 31–32
  - environmental improvements 32, 34
  - and expected capital outlay 34–35
  - fuel usage by well 28–30
  - greenhouse gas emissions from fuel burn 30–31
  - hydraulic fracturing impacts 31
  - net present value (NPV) 34–35
  - waterless fracturing 32–34
  - well lifecycle analysis 17–18
- Shell Middle Distillate Synthesis (SMDS) 437
- Si/Al ratio zeolites 393–394
- simplified Parish and Prausnitz approach (PP) 346, 347, 351
- Sinopec Luoyang's GTA technology 384
- SLE. *see* solid-liquid equilibrium (SLE)
- slickwater fracturing 20, 25, 31, 42
- slurry bubble reactor 441
- Soave equations 347
- Soave-Redlich-Kwong (SRK) EoS 59–60, 121, 345, 352
- SOFC. *see* solid oxide fuel cell (SOFC)
- solid-liquid equilibrium (SLE) 346, 361, 362, 366
- solid oxide fuel cell (SOFC)
  - BOF 511
  - closed-loop validation and results 523
  - cost-contributing factors 511, 512
  - DIR 512–513
  - mathematical model
    - electrochemistry 516–517
    - energy balance 514–515
    - hypothetical model 514
    - kinetics 515
    - mass balance 514
  - mpMPC 519–520
  - natural gas reforming 512
  - PEMFC 511
  - simulation 517–519
- sour gas 282
- sour water stripper (SWS) 187–189
- speed of sound 125–126
- stagnation pressure
  - adiabatic flow 149
  - incompressible 146–147
  - isentropic flow 148–149
  - isothermal flow 147–148
- static pressure 147–148
- statistical associating fluid theory (SAFT) 61–62
- statistical associating fluid theory for fluids
  - interacting through potentials of variable range (SAFT-VR) 368
- steam cracking process 403
- steam methane reforming (SMR) 439
- steam reforming (SR) 512
- stochastic model

- compression performance model 207–208, 217–218
  - for end users 206, 217
  - for mixing stations 205–206, 216–217
  - pipeline performance model 207
  - pressure model 206
  - for sources 204–205, 216
  - stochastic programming approach 197, 330
  - styrene-butadiene latex 403
  - styrene-butadiene rubber (SBR) 403
  - subtractive technology 500
  - sulfur recovery unit (SRU) 184–186
  - supercritical fluids (SCF) in FT synthesis
    - alternate separation design 450, 451–452
    - heavy components first separation 448–451
    - process design approach 445–447
    - product cuts 444–445
    - products upgrading 442–444
    - reactor conditions 445, 446
    - three-phase separator 455
    - vapor and liquid components separation 455–460
    - water first separation 452–456
  - support vector machine (SVM) 533–534
  - sustainability assessment 296–300
  - sweet gas 263, 282
  - Synfuels' cracking of methane to ethylene 404
  - Synfuels process
    - additive technology 500
    - arrangement for 501, 502
    - biofuels 505–507
    - definition 500
    - vs. Fisher-Tropsch 502, 503
    - location 505
    - pilot plant 503–505
  - syngas 219
    - conversion to hydrocarbons 478–479
    - gas-to-liquids (GTL) 466
    - generation 439–440
  - synthetic gas condensates (SGC)
    - dew point predictions for 72
    - gas condensate 71–72
    - molar compositions of 71
  - synthetic jet fuel
    - ANN 528
    - experimental verification of model predicted data 540–542
    - Fischer-Tropsch synthesis process 527
    - hydrocarbon groups 528
    - multivariate regression model, blend property correlation
      - PLS for linear regression model 531–533
      - SVM for nonlinear regression 533–534
    - optimal blend selection using multivariate statistics
      - composition property correlation 537–539
      - hydrocarbon component 535–536
      - reliability prediction using score plot 538–540
    - optimal blend selection using ternary diagram 534
    - PCA 529–531
    - SPK 527–528
  - synthetic natural gases (SNGs)
    - compositions of 67
    - natural gas dew points 65–67
  - synthetic paraffinic kerosene (SPK) 527–528
  - system equations, in piping networks 151
- t**
- tail gas treatment unit (TGTU) 186–187
  - tanks 182–183
  - temperature climate grades of diesel fuel 435
  - temperature effects, in two-phase gas-liquid flow 166–167
  - temperature programmed desorption (TPD) 484
  - ternary systems of NG components with water 351–356
  - thermodynamic analysis, propane refrigeration system 244–245
  - thermodynamic models
    - CPA 344–346
    - GERG-water
      - EoS 343–344
      - pure component parameters 347–348
    - NG components with water
      - and alcohols 360–367
      - binary systems of 347–351
      - and glycols 367–372
      - systems with  $\geq 4$  355–360
      - ternary systems of 351–356
    - PC-SAFT EoS 61–63
    - Peng-Robinson EoS 61
    - physical properties 57
    - software packages 343
    - UMR-PRU model 63–64
    - vdW-P hydrate model 346–347
  - thermodynamics of fluids
    - equation of state 120–121
    - first law of thermodynamics 117–118
    - heat capacity 118–119
    - perfect gas properties 119–120
    - second law of thermodynamics 118, 137
  - three-phase separator (3-PHASE2) 455

threshold limiting value (TLV) 318  
 total dissolved solids (TDS) 20  
 total energy balance 125  
 total organic content (TOC) 472  
 total pressure 146–149  
 transferable potentials for phase equilibria  
 (TraPPE-UA) 479  
 transition state theory (TST) 471  
 true vapor pressure (TVP) 76  
 turboexpander 237, 242  
 two-phase gas-liquid flow  
   adiabatic flow 170–171  
   Dukler and Taitel method 162–164  
   effect of change 167  
   homogeneous flow model 165–166  
   isentropic flow 168–170  
   isothermal flow 167–168  
   pressure drop in 164–165  
   temperature effects 166–167

## U

ultimately recoverable resources (URR)  
   509  
 ultra low sulfur diesel (ULSD) 414  
 unconventional gas 17  
 unity bond index quadratic exponential potential  
 (UBI-QEP) method 480  
 universal force field (UFF) 479  
 universal gas constant 119  
 universal mixing rules (UMR) 64  
 Universal Mixing Rules—Peng Robinson UNIFAC  
 (UMR-PRU) 60–64  
 UOP's methane conversion to butadiene 404  
 upper flammability limit (UFL) 326  
 upstream sector  
   compressor/pump stations 180  
   down hole PVT 175–176  
   methanol/ethylene glycol injection 180–182  
   oil and gas processes 174  
   pipeline modeling 178–180  
   tanks 182–183  
   well site model 176–178  
 U.S. Chemical Safety and Hazard Investigation Board  
   323  
 U.S. Department of Energy 509  
 U.S. Energy Information Administration  
   509  
 U.S. National Transportation Safety Board (NTSB)  
   308

## V

Valderrama modification of the Patel and Teja  
   equation of state (VPT) 348, 373  
 van der Waals family of EoSs 59  
 van der Waals one fluid (vdW1f) 60, 62  
 van der Waals-Platteeuw (vdW-P) hydrate model  
   346–347  
 van't Hoff-type temperature dependence 347  
 vapor cloud explosion (VCE) 320  
 vapor-hydrate equilibrium (VHE) 349  
 vapor-ice equilibrium (VIE) 345, 349, 353  
 vapor-liquid equilibrium (VLE) 349  
 vapor-liquid-liquid equilibrium (VLLE) 365, 366,  
   368  
 vena contracta 155  
 Venturi tube 156  
 volatile organic compound (VOC) emissions 176

## W

wastewater disposal wells 22  
 wastewater injection 21  
 wastewater management 29  
 wastewater treating 27  
 water and seismic impacts  
   recycling produced water 26–27  
   waterless fracturing 24–26  
 water condensation 341  
 water dew point temperature 341  
 waterless fracturing  
   assumptions 33  
   carbon dioxide fracturing 25–26  
   environmental remediation options 32–34  
   impact of 40–41  
   liquefied petroleum gas fracturing 25  
   water and seismic impacts 24–26  
 well lifecycle analysis 17–18  
 well site model 176–178  
 Weymouth formula 142

## Y

Young's modulus 105

## Z

Z forming process 384  
 zinc 389–391  
 Zn-doped SSZ-13 393  
 Zn-doped ZSM-5 catalysts 396  
 ZSM-5 zeolite 383–385