

Index

Note: Page number followed by italics are for figures and bold are for tables, respectively.

- abdominal imaging
 - aliasing along the phase axis of abdomen, *256*
 - entry-slice phenomenon (ESP) in, *283, 283–5*
 - out-of-phase signal cancellation in image of abdomen, *266*
 - phase mismatching in, *243*
 - using balanced gradient-echo, *121*
- acceleration factor, *203*
- acoustic gradient noise, *336*
- active shielding, *327*
- active shimming, *330*
- ADC
 - in brain, **53**
 - in diffusion imaging, *54*
 - extracellular space and, *52*
- adrenal tumors, out-of-phase imaging of, *268*
- algorithms, *203*
- aliasing, *170–1, 173, 232, 261, 277*
 - appearance, *253–4*
 - calculating, *255*
 - causes, *254*
 - FOV in, *253–4*
 - frequency wrap, *254*
 - in *k*-space, *203*
 - phase wrap, *255*
 - remedy, *255–61*
 - velocity-encoding (VENC) gradients, *307*
- alignment of nuclei, *6–7, 8*
 - antiparallel, *7*
 - classical theory explanation, *6, 6–7*
 - parallel, *7*
 - quantum theory explanation, *7, 8*
- American College of Radiology (ACR)
 - levels of personnel, *348*
 - safety zones, definition, *347–8, 348*
- American Society for Testing and Materials International, device-labeling icons, *349, 349*
- amplitude modulation, *167*
- analog, *167*
- analog-to-digital conversion (ADC), *167*
 - watch analogy and, *167*
- analog watches, *167*
- aneurysm clips, *270, 355, 368*
- angiograms
 - 2D sequential inflow, *299–300*
 - 3D volumetric inflow, *300*
- angular momentum, *4*
- anisotropic voxel, *236*
- antialiasing, *257–8*
 - along frequency axis, *257, 257*
 - along phase axis, *257, 260*
- anti-foldover (no phase wrap), *257*
- antiparallel alignment, *7*
- aorta
 - phase-contrast MRA of, *305*
 - spatial presaturation pulses for imaging, *295*
 - swapping phase and frequency in imaging of, *246*
- array processor, *280*
- artifacts
 - aliasing, *253–61*
 - bas-relief, *262*
 - chemical shift, *261–4, 265*
 - cross-excitation/cross-talk, *273–5*
 - from data acquisition errors, *280*
 - from equipment faults, *280*
 - flow, *280–3*
 - magic angle, *279–80*
 - magnetic susceptibility, *269–72*
 - Moiré, *277–9*
 - out-of-phase signal cancellation, *265–9*
 - phase mismatching or ghosting, *243–53*
 - remedies for, **296–7**
 - shading, *276–7*
 - truncation, *272–3*
 - zipper, *275–6*
- asphyxiation, *366*
- asymmetric FOV, *234–5*
- atomic number, *2*
- atomic weight, *2*
- atoms, *2, 6*
 - electrical charge of, *2*
 - motion in, *2–4, 3*
 - structure of, *2*
- Avogadro's law, *9*
- axial images
 - frequency-encoding gradients, *142*
 - phase-encoding gradients, *147*
- balanced gradient-echo, **122**
 - advantages and disadvantages, *121*
 - balanced gradient system in, *119, 119*
 - of lumbar spine, *121*
 - maintenance of steady state in, *120*
 - mechanism, *119–20*
 - parameters, *122*
 - steady state in, *120*
 - uses, *121*
- balanced gradients, *336*
- bandwidth, *139*
 - per pixel, *144*
- bas-relief artifact, *262*
- bellows, *248, 249*
- B_0 (external magnetic field), *8, 25, 313, 325*
 - in Boltzmann's equation, *7*
 - B_1 vs, *15*
 - Larmor frequency vs, *10*
 - number of spins and, *9*
- b* factor/value, *54, 56*
 - in DWI, *54*
- B_1 field, *8, 25, 337*
 - B_0 vs, *15*
- bipolar gradient, *93*
- birdcage design, *339*
- black-blood imaging sequences, *303–4, 304*
 - advantages, *304*
 - in cardiac imaging, *304*
- blipping, *204*
- blood oxygenation level dependent (BOLD) technique, *54, 325*

- blurring, 125
- Boltzmann equation, 7
- bone
 - STIR, 83
 - T1 contrast of, 43
- brain, 356
 - ADC values in, **53**
 - axial 3D inflow MRA images of, 298
 - axial gradient-echo image of, 215–16
 - axial reverse-echo gradient-echo in, 115, 115
 - axial T2-weighted FLAIR of, 84, 85
 - axial T1-weighted inversion recovery sequence of, 81
 - BOLD images of, 55
 - 3D inflow MRA images of, 298
 - Ernst angle graphs of, 102
 - fMRI of, 54, 325
 - hemorrhage, 300
 - midline sagittal T1-weighted image of, 51
 - number of signal averages (NSA) of sagittal, 219
 - sagittal image of, 219, 223–5, 253
 - showing aliasing or wrap around, 253
 - T1 and T2 relaxation times and signal intensity of, **101**
 - T2 decay times of, **29**
 - T1 recovery times of, **26**
- breath-hold images, T1-weighted, 111
 - brightness of pixel, 221
- bucking coils, 327
- burns
 - prevention during MRI, 360
 - RF-related, 358, 368
- carbon (C¹³), **5**
- cardiac pacemakers, risk of damage/ malfunction during scanning, 353, 355–6, 362–3
- cardiac triggering, 252
- carrier frequency, 139
- Cartesian filling, 162
- Cartesian *k*-space filling method, 165
- cerebrospinal fluid (CSF), 31
 - ADC values, **53**
 - T1 and T2 relaxation times and signal intensity of, **101**
 - T2 decay times of, **29**
 - T1 recovery times of, **26**
- cervical spine, 342
 - balanced gradient-echo imaging of, 121
 - sagittal imaging of, 248
 - T2* vs true T2 in images of, 113
- chemical shift, 228
- chemical shift artifact, 261, **265**
 - appearance, 261–2
 - causes, 262–4
 - pixel shift vs, 263, 264
 - reducing receive bandwidth for eliminating, 264
 - remedy for, 264
- chest of drawers analogy, 69, 160, 160–1, 164, 195, 203
- data acquisition type and, 206
- explanation of *k*-space and scan time, 190
- rectangular FOV and, 234–5, 236
- size of FOV and, 192
- children
 - open system scanner for, 316
 - psychological effects during scanning, 351
- chronaxie value, 363
- classical theory, 1, 4–5
 - direction of magnetic moments of spins, 7
- closed-bore systems, 316
- clothes sorting exercise, 161
- co-current flow, 282
- coherent magnetization, 15, 18–20, 26, 31, 91, 210
- coherent or rewound gradient-echo, **110**
 - of abdomen, 108
 - advantages and disadvantages, 109
 - echo formation in, 117
 - of knee, 108
 - mechanism, 106
 - parameters, 107–9
 - uses, 107
- coils
 - bucking, 327
 - coil position vs signal-to-noise ratio (SNR), 212
 - filling factor of, 339
 - gradient, 129, 131
 - head, 343
 - phased array, 211
 - quadrature, 211
 - RF homogeneity of, 339
 - RF receive, 340–3
 - RF transmit, 339
 - surface, 211
 - surface RF receive, 341–3
 - volume RF receive, 343
- compensatory gradients, 151
- computer system and graphical user interface, 344–5
- conjugate symmetry, 184
- contrast agents, 56–7
 - contrast-to-noise ratio (CNR), 227
- contrast-enhanced magnetic resonance angiograms (CEMRA), 298, 309
- contrast-to-noise ratio (CNR), 209
 - contrast agents, 227
 - definition, 226
 - factors affecting, 226–7
 - flow-related techniques, 227–8
 - magnetization transfer contrast (MTC), 227
 - optimization of, 232
 - T2-weighted images in, 227
 - using presaturation pulses, 228–32
- conventional spin-echo, 64, **67**
 - advantages and disadvantages, **67**
 - mechanism, 65
 - parameters, 67
 - spatial encoding in, 68
 - uses, 66
 - using one echo, 65, 65
 - using two echoes, 65–6, 66
- counter-current flow, 282
- cross-excitation/cross-talk, 273–5, 274
 - appearance, 273
 - causes-275, 273
 - remedy for, 275
- cryogenics (coolants), 320, 322
 - asphyxiation risk, 366
 - explosion risk, 367
 - quenching risk, 366–7
 - thermal sensitivity from, 365–6
- cryostat, 320–1, 321
 - physical construction of, 321, 321
 - primary function of, 321
- Curie temperature, 315
- dance analogy, 59
- data points, 164
- dead time and T1 recovery, 154
- dephasing, 28, 29
- diamagnetic compounds, 313
- diamagnetism, 313–14, 314
- diethylene triaminepentaacetic acid (DTPA), 56
- diffusion, 52, 53
- diffusion weighted imaging (DWI), 52–4, **56**
- digital sampling frequency, 169–71, 179
 - in terms of Nyquist frequency, 173
- digital sampling rate, 169
- digital watch, 167
- digitization of analog signal, 167
- discs, ferromagnetic, 318
- Dixon technique. *see* out-of-phase imaging (Dixon technique)
- Double Echo Steady State (DESS), 125
- double IR prep, 87
- driven equilibrium (DRIVE), 77, 77
- 2D sequential inflow angiograms, 299–300
- dual echo spin-echo sequences, 66
- duty cycle, 333
- 3D volumetric inflow angiograms, 300

- ECG-triggered 3D FSE, 308–9
- echo planar imaging (EPI), 122–4
 advantages and disadvantages, **126**
 contrast parameters, **126**
 uses and limitations, 124–7
- echo-spacing, 73
- echo time (TE), 22, 29
 magic angle artifact and, 280
 relationship between receive
 bandwidth, frequency matrix, and,
 174–6, **177**, **177**
 resolution, effects of, 234
 slice number and, 178–9
 susceptibility artifact and, 271
 truncation artifact and, 272
- echo train, 68, 69
 full, 73
 shared, 73
 split, 73
- echo train length (ETL), 68
- eddy currents, 331
- EKG-triggered subtraction imaging,
 308–9
- electrocardiogram (ECG, EKG) gating,
 252
- electromagnetic (radiofrequency) fields,
 hazard effects of
 antenna effect, 360–2
 deterministic effects, 357
 patient heating/burns, 358–60
 temporary or permanent changes to
 implanted devices, 362–3
- electromagnetic spectrum, 12
- electromagnetism, 313
- electromotive force (emf), 18–19
- entry-slice phenomenon (ESP), 280–3,
 281–2, 284–5, **285**
 direction of flow, 282, 283
 flip angle, 282
 flow velocity, 282
 slice thickness and, 282
 TR in, 282
- Ernst angle, 101, 102
- even-echo rephasing, **296**
- extremity scanners, 317
- extrinsic contrast parameters, 25, 226
 T2* contrast and, 102
- Faraday's law of electromagnetic
 induction, 4–5, 18–19, 129, 313,
 320, 352
- Fast Fourier Transform (FFT), 156,
 158–9, 178, 179–83
- fast gradient-echo, 122
- fast or turbo spin-echo (FSE/TSE), 64,
76
 advantages and disadvantages, **73**
 different rephasing angles in, 78
- filling of *k*-space, 69
 mechanism, 68–9
 parameters, 73–5
 PD-weighted image of a knee, 75 ?
 TR selection in TSE, 76
 T2-weighted image of a female pelvis,
 72
 T1-weighted image of a male pelvis,
 74
 uses, 72–3
 weighting in TSE, 70–1
- fat
 chemical shift artifact of, 262
 hyperintensity of, 328
 magnetic moments of, 33, 178, 228,
 230–1, 262, 265, 269
 molecules, 32
 out of phase magnetic moments of,
 269
 partial saturation of, 36
 periodicity of, 268
 saturation, 228, 228–9
 suppression, 83, 273, 326
 T2 decay in, 34
 T1 recovery in, 33
 T1 recovery time of, 36
- ferromagnetic compounds, 314
- ferromagnetism, 314–15, 315
- field of view (FOV)
 chest of drawers analogy and size of,
 192
 distance between each data point
 and, 196–7
 frequency, 144–5, **151**, 194–5
 frequency encoding and, 144–5
 half FOV ghosts, 125
k-space, 191–5
 phase, 192–5
 pixel dimension and, 233
 receive bandwidth for whole, 178
 rectangular, 234–5
 resolution and, 234
 size of, 191–2, 194
 voxel dimensions and, 221, 223
- field strength (flux density), 325
- filling factor of a coil, 339
- filling options for *k*-space, 199–206,
200
 in EPI, 204
 NSA controls, 190–1, 215
 parallel imaging, 201–3, 202
 partial echo, 201, 202
 partial or fractional averaging or half
 Fourier, **200**, 200, 200–1
 propeller, 205
 radial, 205
 single-shot (SS) imaging, 204–5
 spiral, 205, 205
- fine matrix, 233
- first-order motion, 290
 compensation, 293
- first spin-echo, 66
- flip, 16
- flip angle
 entry-slice phenomenon (ESP), 282
 gradient-echo pulse sequences, 90
 signal-to-noise ratio (SNR) vs,
 214variable, 90
- flow artifacts, 280–3
 entry-slice phenomenon (ESP),
 280–3, 284–5
 flow-related enhancement of signal,
 280
 high-velocity signal loss, 280
 time-of-flight (TOF) phenomenon,
 280, 285–90
- flow compensation techniques, **296**
 even-echo rephasing, **296**
 gradient moment rephasing (gradient
 moment nulling), 291–3, 292
 spatial presaturation pulses, 293–5,
 294, 296
- flow-dependent (non-contrast-enhanced)
 angiography
 benefit of, 298
 2D sequential inflow angiograms,
 299–300
 3D volumetric inflow angiograms, 300
 inflow MRA, 298–9, **303**
 scan time, 298
- flow-related enhancement, 281, 281
- flow-related techniques, 227–8
- flow-spoiled fresh blood imaging,
 308–9
- flow velocity
 in entry-slice phenomenon (ESP), 282
 in time-of-flight (TOF) phenomenon,
 287
- fluid attenuated inversion recovery
 (FLAIR), **60**, 64
 of brain, 85
 EPI-FLAIR, 123
 gadolinium and, 86
 mechanism, 84
 parameters, 86–7
 uses, 85
- flux density, 325
- fold-over suppression (no phase wrap),
 257
- foreign bodies, risk from, 357
- free induction decay (FID) signal, 21,
 29, 29, 153
- frequency encoding, 135, **145**, 151
 FOV and, 144–5
 keyboard analogy and, 143
 procedure, 142
 rephasing mechanism in, 142–3
 timing of, 142, 144

- frequency FOV, 144–5, **151**, 194–5
 frequency matrix, 144, **151**, 164, **177**,
 178–9, 184, 191, 193–4, **196**,
 208, 233–4
 of 10, 172
k-space and, 167–8
 relationship between TE, receive
 bandwidth, and, 174–6, **177**, **177**
 scan time and, 238
 sprinter analogy and, 171–2
 frequency modulation, 167
 frequency resolution
 in *k*-space, 193
 frequency wrap, 254
 fringe field, 318
 functional MRI (fMRI), 54–5, **55**, **56**,
 325–6
- gadolinium (Gd), 56, 315
 contrast-enhanced magnetic resonance
 angiograms (CEMRA), 298
 ferromagnetic nature of, 315
 FLAIR and, 86
 incoherent or spoiled gradient-echo
 sequences, effect in, 111
 in IR pulse sequences, 81
 SPIR vs STIR sequences, 231
 gating, 250
 in cardiac imaging, 252
 electrocardiogram (ECG, EKG), 252
 gauss (unit), 132, 325, 335
 ghosting artifact. *see* phase mismatching
 gradient amplifiers, 332–3
 gradient amplitude, 133
 gradient axes, 134–5
x gradient, 134
y gradient, 134
z gradient, 134–5
 gradient coils, 129, **131**, 331–2, **332**
 gradient-echo, 93
 gradient-echo EPI (GE-EPI), 122, **123**
 gradient-echo pulse sequences, 58, 89,
93, **94**, **127**
 classification of, 106
 coherent or rewound gradient-echo,
 106–9
 common acronyms, **90**
 comparison of single-shot and
 multishot techniques, **123**
 extrinsic parameters, **99**
 gradient rephasing, 91–3, **92**, **94**
 parameter selection in, 119
 variable flip angle, 90
 vs spin-echo pulse sequences, 90
 weighting mechanisms in, 94–106
 gradient labeling, **135**
 gradient moment rephasing (gradient
 moment nulling), 253, 291–3, **292**
- gradient off-set (dynamic) shimming, 330
 gradient polarity, 129, **130**
 gradient power duty cycle, 335
 gradients, 8, 129
 field strength and precessional
 frequency, changes in, **130**, **132**
 mechanism of, 129–33, **133**
 in pulse sequence diagrams, 134
 steep and shallow gradient slopes,
 133, **133**
 watch analogy and, 132
 gradient spoiling, 91, 111
 gradient system, 330–7
 acoustic gradient noise, 336
 balanced gradients, 336
 characteristics of a magnetic field
 gradient, **334**
 field strength, 333
 gradient amplifiers, 332–3
 gradient amplitude, 334–5
 gradient coil, 331–2, **332**
 gradient power duty cycle, 335
 gradient rise time, 335
 gradient slew rate, 335
 graphical user interface, 344–5
 GRASE (gradient- and spinecho), 124,
124
 gray matter, ADC values of, 52, **53**
 gyromagnetic ratio, 10
- Hahn echoes, 105
 half Fourier, 199–201
 half FOV ghosts, 125
 head coils, 343
 headphones, **364**
 heart
 balanced gradient-echo imaging of, 121
 gating in cardiac imaging, 252
 IR prep sequences of, 87
 phase encoding axis, 246
 heat analogy, 48, **49–50**
 weighting in gradient-echo using, 97,
98–9
- Heisenberg's Uncertainty Principle, 2
 helium dewar, 366
 high-energy nuclei, 7
 homogenous magnetic field, 328
 human body, common elements in, **5**
 hybrid sequences, 124
 hydrogen, 2
 energy states of, 7
 in fat, 33
 gyromagnetic ratio of, 10
 magnetic characteristics of, **12**
 nucleus/nuclei, 5, 7
 value of *S* for, 8
 hydrogen nuclei, magnetic moments of,
 5, 6–7, 64, 148, 152, 182, 328,
338
- Boltzmann's equation, 7
 direction of, in classical and quantum
 theory, 7
 precessional frequency of, 130–1
- image blurring, 73, 125
 image contrast in diagnostic imaging,
 25, **56**
 contrast agents, 56–7
 contrast mechanism, 31–2
 extrinsic contrast parameters, 25
 functional MRI (fMRI), 54–5, **55**,
56
 intrinsic contrast parameters, 25
 magnetization transfer contrast
 (MTC), 55
 proton density contrast of tissues, 41
 relaxation, 25–6, 32–5
 signal intensity of a tissue, 41
 susceptibility weighting (SWI), 55
 T1 contrast, 36
 T2 contrast, 40–1, **41–2**
 T2 decay, 26–31, **28**
 T1 recovery, 26–7, **27**
 weight image contrast, 42–8
 image matrix, 221
 in *k*-space, 233
 number of pixels in the FOV and, 233
 voxel size and, 233
 voxel volume and, 221
 incoherent or spoiled gradient-echo,
112, **113**
 advantages and disadvantages, **113**
 echo formation in, **118**
 mechanism, 109–11
 parameters, 111
 spoiling methods, 110–11
 uses, 111
 inflow MRA, 298–9, **303**
 advantages and disadvantages, **300**
 overcoming advantages of, **300**
 in phase (coherent), 13, **15**
 inter-view mismatching, 245
 intravoxel dephasing, 290, **291**
 intrinsic contrast parameters, 25, 226
 inversion recovery (IR), 64, **87**
 advantages and disadvantages, **85**
 fast, 82
 image reconstruction in, 87
 180° inverting pulse in, **79**
 mechanism, 78–80
 parameters, 81–2
 PD weighting in, **80**
 prep sequences, 87
 sequence, **79**
 T1 weighted, of brain, **81**
 T1 weighting in, **80**
 uses, 81

- ionization, 2
- ions, 2
- isotopes, 2
- isotropic voxel, 235

- J-coupling, 72
- joint imaging
 - using balanced gradient-echo, 121

- k*-space, 68–70, 73
 - central lines of, 184, 186
 - chest of drawers analogy and, 69, 160, 160–1
 - contrast lines of, 186
 - data acquisition and image creation in, 165–83
 - data arrangement in, 164
 - data points vs photographs, 169
 - definition, 159
 - digital sampling frequency, 169–70
 - filling and phase reordering, 71
 - filling methods, 159, 161–2, 164
 - filling options, 199–206, **200**
 - FOV dimensions, 233
 - frequency axis of, 159, 160, 192, 194
 - frequency FOV, 192–5
 - frequency matrix, 168, 193
 - frequency resolution, 193
 - grid of data points in, 167, 168, 184
 - image matrix in, 233
 - labeling, 163
 - lines of, 161
 - meaning of *k*, 159
 - multiple noise spikes, 277
 - negative and positive halves of, 200
 - phase axis of, 159, 160, 182, 192, 194
 - phase-encoding gradient and, 163–5
 - phase FOV, 192–5
 - phase gradient amplitude vs signal amplitude, 186
 - phase matrix, 168, 190, 193, 233
 - phase mismapping and, 245
 - pixel size, , 193–5, 233
 - positive polarity phase-encoding gradients, 161
 - pulse sequences, 197–9
 - respiratory compensation and, 248, 249–50
 - sampling window, 167, 169–72
 - scan time to fill, 188–91
 - sequential and 3D (volume)
 - acquisition of data in, 206–8
 - signal and resolution of image, 185–7, 186–7
 - signals from one voxel, 180
 - in a single shot, 204
 - size of FOV, 191–2, 194
 - slice-select gradient application, 164–5
 - spatial resolution, 193
 - symmetrical features, 182, 184, 185
 - units of, 159
 - using signal data only, 188
 - vs spatial frequency, 159
 - waveforms, 166180

- laminar flow (parabolic flow), 288–90
- Larmor equation, 10
- Larmor Grand Prix analogy, 62, 63
- Lenz's law, 19
- level 1 personnel, 348
- level 2 personnel, 348
- lipids, 32
- liquid helium, 322
 - risks from, 365–7
- liver
 - ADC values, 52
 - nulling of signals in, 231–2
- lobes, 134
- longitudinal and transverse magnetization, 21
- longitudinal plane, 7
- Lorentz force, 328, 336, 352
- low-energy nuclei, 7

- magic angle artifact, 279–80
 - appearance, 279
 - causes, 279–80
 - in collagen rich tissues, 279–80
 - echo time and, 280
 - of patellar tendon, 279
 - remedy for, 280
- magnetic flux density, units of, 132
- magnetic homogeneity, 343
 - in MRI, 328–9
- magnetic isocenter, 129, 132–3
 - location of pixel at, 182
- magnetic moment, 4, 9, 13–14
- magnetic moments of fat nuclei
 - inversion of, 230
 - precessional frequency of, 228, 231
 - saturation of, 228
- magnetic resonance angiography (MRA)
 - flow-dependent, 309
 - inflow, 298–9, **303**
 - pulse sequence parameters, 309
- magnetic resonance imaging (MRI)
 - classical theory in, 1
 - components of, 312
 - computer system and graphical user interface, 344–5
 - extrinsic contrast parameters, 25
 - fat and water, 32, 32–3
 - frequency encoding in, 143
 - fundamentals of, 1
 - geometric accuracy of, 269–70
 - image contrast in, 24
 - intrinsic contrast parameters, 25
 - k*-space filling methods in, 161–2
 - magnetic field homogeneity in, 328–9
 - patient transport system, 343–4
 - principles of, 2
 - scanners, 311–12, 312
 - slice-selection in, 138
 - thermal equilibrium in, 9
 - voxel geometry and pixel dimension, 233
- magnetic susceptibility, 313
- magnetic susceptibility artifact, 269–71
 - appearance, 269
 - causes, 269–70
 - of a dental implant, 270
 - echo time and, 271
 - of knee, 271
 - receive bandwidth and, 271
 - remedy, 270–2
 - spin-echo sequences and, 270, 272
- magnetism, **313**, 313–15
 - diamagnetism, 313–14
 - ferromagnetism, 314–15
 - paramagnetism, 314
- magnetization transfer contrast (MTC), 55, 227
- magnet shielding
 - active, 327
 - passive, 326–7, 327
- magnet system, requirements of
 - field strength, 318
 - fringe field, 318
 - homogeneity aspect, 318
 - weight and bulk of magnet, 318
- magnitude images, 307
- mass number, 2, 4
- maximum intensity projection (MIP), 300–1, **301**
- Moiré artifact, 277–9
 - appearance, 277–9
 - field inhomogeneity, 277–9
 - multiple noise spikes, 277, 278
 - as zebra lines, 277, 278
- molecules, 2
- MR active nuclei, 4–5, 10
 - magnetic moments of, 12
- multiple overlapping thin slab acquisitions (MOTSA), 302, **302**
- muscle, 31
 - cardiac, 363
 - images in steady-state sequences, 100
 - magnetization transfer effects of, 72
 - rheobase, 363
 - T1 recovery and T2 decay times, 102

- negative lines, 161
 neodymium magnets, 318
 net magnetic vector (NMV), 7–9, 9, 21, 26, 31, 61, 79–80, 82, 90
 of fat, 33
 fully saturated, 36
 partially saturated, 36
 signal-to-noise ratio (SNR), effect on, 9
 of water, 33
 neurostimulators, risk of damage/
 malfunction during scanning, 355
 neutrons, 2
 nitrogen (N^{15}), **5**
 magnetic characteristics of, **12**
 noise, 210
 non-MRI personnel, 348
 nucleons, 2
 null point, 82
 number of signal averages (NSA),
 190–1, **196**
 multiple, 252
 phase mismapping and, 258
 of sagittal brain, 219
 scan time and, 237
 nutation, 14
 Nyquist frequency, 171
 Nyquist theorem, 170, 170
- Ørsted, Hans Christian, 313, 319
 open systems, 316
 optimal saturation, 230
 optimizing image quality, **239**
 out-of-phase imaging (Dixon technique),
 232, 268
 out of phase (incoherent), 13, 15
 out-of-phase signal cancellation, 265–9
 appearance, 265
 benefits of, 268
 causes, 265
 watch analogy and, 266, 267
 oxygen (O^{17}), **5**
 magnetic characteristics of, **12**
- PACS (picture archiving and
 communications system) access
 network permitting teleradiology,
 345
 parallel alignment, 7
 parallel imaging, 201–3, 202
 paramagnetic compounds, 314
 paramagnetism, 314, 314
 partial averaging, 200–1
 partial echo, 201, 202
 partial voluming, 232
 passive shielding, 326–7, 327
 passive shimming, 329–30, 330
 pathology weighting, 82
- patient transport system, 343–4
 PD weighting, in coherent gradient-
 echo, 109
 peripheral pulse triggering, 252
 permanent magnet MRI scanners,
 318–19, 319
 permanent magnets, 316
 phase, 13
 phase-contrast angiography, 304–7, **307**
 advantages and disadvantages,
 305–7, **307**
 gradient, 305
 phase-contrast MR angiography, 228
 phase encoding, 135, 146, **151**, 179
 amplitude and polarity changes in,
 149–50, 153
 of axial images, 147
 of coronal images, 147
 long and short axis of anatomy, 147
 phase matrix and phase resolution in,
 149–50
 phase shift along the gradient, 155,
 156
 procedure, 145–7
 of sagittal images, 147
 selection of direction, 147
 spatial frequencies in, 155–6, 156,
 158
 steep and shallow gradients, 149,
 149–50
 timing of, 148, 148–9
 watch analogy and, 147
 phase FOV, 194–5
 phase images, 307
 phase-locked circuit, 110
 phase matrix, 149–50, **151**
 scan time and, 237
 phase mismapping, 232, 243–53, **253**
 appearance, 243
 cause, 244, 244–5
 equation, 243
 gradient moment rephasing for
 reducing, 253
 image through a breathing abdomen,
 243
 k-space and, 245
 multiple NSA for reducing, 252
 phase-encoding gradient, 244
 presaturation pulses for reducing, 248
 remedy for, 245–53
 respiratory compensation for reducing,
 248–9
 respiratory gating and triggering for
 reducing, 250–1, 251
 swapping phase and frequency for
 reducing, 246
 phase oversampling (no phase wrap), 257
 phase reordering, 72
 phase resolution, 149–50, **151**
- phase wrap, 255
 pixel, 129, 221
 pixel dimension, 233
 pixel size
 frequency, 194, **196**
 in *k*-space, 233
 phase, 194–5, **196**
 polarity of gradient, 93
 pole shoes, 318
 precession, 10, 11
 spin-up and spin-down populations,
 11
 precessional (Larmor) frequency, 10,
 13–14, 33, 55, 128, 139, 148
 between fat and water, 228
 gyromagnetic ratio, 10
 of hydrogen, 31
 Larmor equation, 14
 magnetic field strength and, 28–9,
 130, 130, 135
 of magnetic moments of fat nuclei,
 228
 of magnetic moments of hydrogen
 nuclei, 34, 103, 130–3, 135–6,
 139, 142, 145–7, 228
 shallow gradient slopes, effect of,
 133
 slice-select gradient and, 136, 139
 precessional path, 10
 presaturation pulses, 228–32, 293–5,
 294, 296
 for reducing phase mismapping, 248
 projectile hazards, 352–5, 353–4
 propeller *k*-space filling, 205
 protium, 5, **5**
 protocol (s)
 characteristics, 209–10
 definition, 209
 modification, 238–41
 optimization of, 210
 proton density contrast of tissues, 41
 examples, **47**
 proton density (PD) of a tissue, 31
 proton density weighting, 46, **48**
 of ankle, 47
 heat analogy, 50
 protons, 2
 pseudo-frequency, 180
 psychological effects of MRI, 350–1
 pulsatile flow, 293
 pulse generator module (PGM), 344
 pulse sequence, 22, 22, 25
 pulse sequences, 21, 58
 definition, 59
 diagram, 59
 pulse sequence timing, 152–4
 pulse timing parameters, 22
 pulse width modulated (PWM) design,
 332

- quantum theory, 1, 7
 quenching, 354, 366–7
- radial *k*-space filling, 205
 radian (s), 13, 159
 radio frequency (RF), 12
 radio frequency (RF) excitation pulse,
 14–15, 29, 128
 dummy pulses, 37
 magnetization in water, effect on, 36
 preparatory, 37
 ramped RF, 302
 ramped sampling, 122
 ramping a magnet, 323, 324
 rare-earth magnets, 318
 RARE (Rapid Acquisition with
 Relaxation Enhancement), 68
 readout or measurement gradient, 142,
 167
 receive bandwidth, 144, 172–4
 parameters of different
 manufacturers, 178
 reducing for eliminating chemical
 shift artifact, 264
 reducing of, 220–1
 relationship between TE, frequency
 matrix, and, 174–6, **177**, 177
 signal-to-noise ratio (SNR) vs, 220,
 220
 susceptibility artifact and, 271
 for the whole FOV, 178
 rectangular FOV, 234–5
 reduction factor, 203
 relative permittivity, 362
 relaxation, 20, 25–6, **31**
 in different tissues, 32–5
 relaxivity, 56
 renal area, chemical shift artifact of, 262
 repetition time (TR) period, 22, 154
 acceleration factor, 203
 in balanced gradient echo, 120
 in coherent gradient-echo, 120
 entry-slice phenomenon (ESP), 282
 equal infinity, 124
 frequency-encoding gradient in, 183
k-space filling and, 163–5, 189, 201,
 203
 longitudinal magnetization during, 95
 reduction factor, 203
 respiratory gating and triggering,
 effects of, 251
 SAT TR, 230
 scan time and, 237
 signal to noise ratio vs, 213–15
 T1 recovery and, 154
 vs slice number, 189, 189
 resistive electromagnets, 318–20
 resistive MRI scanners, 320
- resonance, 8, 13–16
 resonator, 360
 respiratory compensation techniques,
 248–9, 248–50
 respiratory gating and triggering, 250–1,
 251
 respiratory navigator echoes, 248
 respiratory sensor, 248
 reverse-echo gradient-echo, **114**, **117**
 actual TE, 114
 advantages and disadvantages, **116**
 in brain, **115**
 echo formation in, **118**
 effective TE, 114
 mechanism, 113–14
 parameters, 116–17
 steady-state sequences in, 117–18
 uses, 115
 rewinders, 93
 RF amplifier, 339
 RF homogeneity of the coil, 339
 RF receive system, 339–40
 RF rephasing, 59–62, 64
 180° RF rephasing pulse, 60–1, **61**
 RF rephasing in spin-echo pulse
 sequences, 139, 141
 frequency encoding and, 142–3
 in hybrid sequence, 124
 in spin-echo EPI (SE-EPI), 123
 RF shielding, 337–8
 RF spoiling, **110**, 110–11
 RF system, 337–43
 RF receive coils, 340–3
 RF receive system, 339–40
 RF shielding, 337–8
 RF transmit coils, 339
 surface RF receive coils, 341–3
 transmit system, 338–9
 volume RF receive coils, 343
 rheobase, 363
 right-hand grip rule, 319, 320
 rise time of gradient, 335
 rotating frame of reference, 18
- safety (MRI)
 of devices, 349–50
 MRI conditional, definition, 349
 MRI safe, definition, 349
 MRI unsafe, definition, 349
 of patient, 350
 philosophy behind, 347
 protection of patient's hearing during
 scan, 365
 tips, 367–8
 zones, 347–8
 sagittal brain, using a square FOV, 225
 sampling
 digital sampling frequency, 169–71
 digital sampling rate, 169
- equations, 171
 at less than once per cycle, 170
 once per cycle, 170
 sprinter analogy and, 171–2
 sampling interval, 169
 sampling time, 142
 sampling window, 142, 173–4, **178**, 179
 frequency-encoding gradient in,
 174–5
 impact on TE, 174
 sampling window (acquisition window),
 167
 SAT TR, 230
 saturation, 17
 saturation of fat signal, 228
 saturation pulses, 248
 scanner configurations
 closed-bore systems, 316
 extremity systems, 317
 open systems, 316
 scan time, 68–9, 210
 in flow-dependent (non-contrast-
 enhanced) angiography, 298
 frequency matrix and, 238
 for improving resolution, 238
 NSA and, 237
 optimization, 237
 phase matrix and, 237
 TR and, 237
 sensitivity encoding. *see* parallel
 imaging
 sequential acquisitions of data, 206,
 207
 sequential and 3D (volume) acquisition
 of data in *k*-space, 206–8
 shading artifacts, 276–7
 appearance, 276
 causes, 276–7
 remedy for, 277
 shimming, 328–30
 active, 330
 gradient off-set (dynamic), 330
 passive, 329–30, 330
 shim system, 328–30
 short tau inversion recovery (STIR), **60**,
 64, 308–9
 of knee, **84**
 mechanism, 82–3
 parameters, 84
 pulse sequence, 231
 uses, 83
 sickle-cell anemia, 290
 signal intensity of a tissue, 41
 signal-to-noise ratio (SNR), 209, **226**,
 233
 coil position vs, 212
 definition, 210
 equations, 211
 field strength and, 325–6

- signal-to-noise ratio (*continued*)
 flip angle vs, 214, 214
 magnetic field strength and, 211
 net magnetic vector (NMV), effect of, 9
 number of signal averages vs, 215–18, 218–19
 optimization of, 226
 phased array coils and, 211
 proton density and, 211
 quadrature coils and, 211
 receive bandwidth vs, 220, 220
 relationships between protocol parameters and, **226**
 signal amplitude affecting, 210
 slice thickness vs, 222
 spatial resolution and, 239, 241
 surface coils and, 211
 TE controls vs, 215, 216–18
 trade-offs in, 238, 240
 TR controls vs, 213, 213–15
 T2-weighted images in, 227
 type of coil and, 211
 volume imaging and, 223
 voxel volume vs, 221–3
- single shot fast or turbo spin-echo (SS-TSE), 77, 204
- single-shot (SS) imaging, 204–5
- slew rate, 334–5
- slice encoding, 207
- slice gap, **151, 196**
- slice-selection, 135–9, **141, 151**
 gradients performing, 136, 138
 in MRI system, 138
 procedure, 135–6
 slice thickness and, 139–41, 140
 timing of, 136, 138
 tuning fork analogy and, 136, 137
- slice thickness, 139–41, **151, 196**
 entry-slice phenomenon (ESP), 282
 time-of-flight (TOF) phenomenon and, 287
- solenoid electromagnets, 316–17, 317–18, 323
- solenoid magnets, 319, 322
- space-blanket, 321
- spatial encoding, 129, 161, 230, 270, 352
 in conventional spin echo, 68
 gradient axes, 134–135
 mechanisms of gradients, 129–133
 slice-selection, 135–139
 watch analogy and, 152
- spatial frequency, 155
 musical notes on a piano keyboard, 155
 from slice-selection, 158
 in steep phase-encoding gradients, 155
- vs amplitude of phase-encoding gradient, 155–6, 156
- spatial inversion recovery (SPIR), 230
 STIR vs, 231
- spatial presaturation pulses, 293–5, 294, 296
 for black-blood imaging sequences, 303
- spatial resolution, 210, 232–4, **237**
 in *k*-space, 193
 in MR, 239
 voxel size and, 232
- specific absorption rate (SAR), 78, 346
- spinal imaging
 using balanced gradient-echo, 121, 121
- spine
 flexion and extension views of, 316
 spin-echo, 61
 spin-echo EPI (SE-EPI), 122–3, 123
 of abdomen, 125
 spin-echo pulse sequences, 58, 62, **88**
 common acronyms, **60**
 elimination of T2* dephasing, 61
 gradient timing in, 152–4, 153
k-space filling in, 164
- spin–lattice energy transfer, 26
- spin–spin interaction, 28
- spin–spin relaxation, 27–8
 optimality of, 35
- spiral flow (helical flow), 290
- spiral *k*-space filling, 205, 205
- spleen, nulling of signals in, 231–2
- spoilers, 91
- sprinter analogy, 171–2
- static field of MRI scanner, implications for safety
 foreign bodies, 357
 projectile hazards, 352–5
 torque on implanted devices, 355–7
 transient biological effects, 351–2
- stationary frame of reference, 18
- steady-state, 37, **105**
 echo formation in, 103–6, 104–5
 weighting of steady-state gradient-echo sequences, 100–1, 101, **102**
- stents, risk of damage/malfunction during scanning, 355
- superconducting MRI scanner, 322
- superconductive magnet systems, **326**
 electromagnets, 320–2
- superconductivity, 322
- suppression
 CSF, 84
 fat, 83, 273, 326
 fold-over, 257
 in inflow angiography, 268, **300**
- surface RF receive coils, 341–2, 341–3
- susceptibility weighting (SWI), 55
- T1 agents, 56
- T2 agents, 56
- tau, 60, 64, 64
- T1 contrast, 36, **52**
 achieving steady-state, 37
 examples, **43**
 impact on saturation effects, 36, 38–9
 longitudinal magnetization in fat and water, 36, 37
- T2 contrast, 40–1, **41–2, 52**
 examples, **46**
- T2* contrast, 97
 extrinsic contrast parameters and effect on, 102
 in gradient-echo, 97
 TE controls and effect on, 95
- T2 decay, 26–31, 28, **41, 44, 52, 61, 65–6, 94, 102, 153**
 of brain tissue, **30**
 in fat, 34
 between fat and water, 45
 strength of B_0 and, 35
 in water, 34
- T2* decay, 94
- T2 decay time, 29, **52, 55**
 of fat and water, 40
- T2* dephasing, in spin-echo pulse sequences, 59–61, 60, 61, 62
 in magnetic moments of hydrogen nuclei, 60, 61
- teslas (T), 8, 132, 325
- thermal equilibrium, 7
 spin-up to spin-down nuclei in, 9
- thermal sensitivity, cryogen, 365–6
- three-dimensional (3D) volumetric acquisition (volume imaging), 207–8
- time-of-flight (TOF) phenomenon, 280, 285–90, 286, **288**
 flow velocity, 287
 in gradient-echo pulse sequences, 287
 slice thickness and, 287
 in spin-echo pulse sequences, 286–7
 TE vs, 288
 type of pulse sequence and, 285
 types of flows, 288–90, 289
- time-varying gradient magnetic fields, hazard effects of
 adverse effect on implanted devices, 363
 nerve stimulation, 363
 noise-induced hearing loss, **364, 364–5**
- tip angle, 16
- tissues
 aliasing of, 203
 contrast agents and visualization of, 56
 dephasing between, 271

- diffusion imaging of, 54
- EPI sequences on, 124
- gradient-echo imaging, 95–6
- IR pulse sequences, effect of, 81–2
- magnetization in, 100, 122, 269, 281
- nulling of signals in, 231–2, 293
- proton density of, 211
- RF rephasing effect on, 62, 65
- susceptibility weighting (SWI) of, 55–6
- T1 and T2 relaxation times of, 100, **101**, 103–6
- T2 decay time of, 65–6, 73, 102, 113
- turbo spin-echo imaging, 73
- T2-weighted images of, 56
- TI (time from inversion), 80
- torque on implanted devices, effect on patient, 355–7, **356**
- trade-offs, 210
- transceiver, 339
- transient biological effects, 351–2
- transmit bandwidth, 139
- transverse plane, 14
- traveling SAT band, 299
- T1 recovery, 26–7, **27**, **42**, **52**
 - dead time and, 154
 - in fat, 33
 - between fat and water, 42, **42**
 - in water, 33, **34**
- T1 recovery times, 26, **52**, **81**
 - of brain tissue, **26**
 - of fat, 36
- triggering, 250
 - cardiac, 252
 - EKG, 252
 - peripheral pulse, 252
- triglyceride fat molecules, 262
- triple IR prep, 87
- truncation artifacts, 272–3, **273**
 - appearance, 272
 - causes, 272
 - echo time and, 272
 - remedy, 273
- turbo factor, 68–9
- T2-weighted image
 - of buttock, 227
 - of pelvis, **230–1**
- T1-weighted images, **44**, **52**, 300, 303
 - of brain, **51**
 - breath-hold images, 111
 - chest, **246–7**
 - fat suppression techniques used in, 273
 - heat analogy, **49**
 - of knee, **43**
- T2-weighted images, 44, **46**, **52**
 - contrast-to-noise ratio (CNR) in, 227
 - heat analogy, **49**
 - signal-to-noise ratio (SNR) in, 227
 - of wrist, **45**
- T1 weighting
 - in coherent gradient-echo, 109
- T2* weighting, 94, 124
 - in coherent gradient-echo, 106, 109
 - in gradient-echo and heat analogy, 97, **98**
- two-dimensional (2D) volumetric acquisitions of data, 206, **207**
- ultra-high-field research magnets, 327
- ultra-high-field-strength systems, 327, 351–2
- unpaired electrons, 56, 314–15, 319
- user interface, 344–5
- variable flip angle, 90
- vascular patency, 290
- vectors, 21, 303, 334
 - at different frequencies dephase, **28**
 - extrinsic contrast parameters, effect of, 95
 - fat, 35, 36, 42, 44, 46, 65, 81, 95–6, 265
 - in 180° RF rephasing, **61**
 - RF spoiling effect on, 110
 - water, 35, 36, 42, 44, 46, 65, 81, 95–6, 265
- velocity-encoding (VENC) gradients, 304, **306–7**
- venetian blind effect, 302
- view-to-view mismapping, 245
- volume imaging, 188, 200
 - aliasing in, 261
 - resolution and, 235–6
 - SNR and, 223
 - three-dimensional (3D) volumetric acquisition, 207–8
- volume RF receive coils, 343
- vortex flow, 290
- voxel, 129
- voxel size
 - FOV vs, 233
 - number of pixels or image matrix and, 233
 - slice thickness vs, 232
- voxel volume
 - changes in FOV and, 223
 - image matrix and, 221
 - signal-to-noise ratio (SNR) vs, 221–3, **222**
 - voxel size and slice thickness, 221
- warm bore, 321, **321**
- warning signs, 355
- watch analogy, 17–18, 132
 - change of phase over time, 155
 - out-of-phase signal cancellation and, 266, **267**
 - phase encoding and, 147
 - spatial encoding and, 152
- wrap. *see* aliasing
- water
 - chemical shift artifact of, 262
 - magnetic moments of, 178, 262, 265, **269**
 - molecules, 32
 - net magnetization vector (NMV) of, 33
 - out of phase magnetic moments of, **269**
 - periodicity of, 268
 - saturation, 228, **229**
 - T2 contrast image of, 40, **40**
 - T2 decay in, 34
 - T1 recovery in, 33, **34**
- weight image contrast, 42–8
 - proton density weighting, 46
 - T1-weighted image, 42. *see also* T1-weighted images
 - T2-weighted image, 44. *see also* T2-weighted images
- weighting mechanisms in gradient-echo pulse sequences, 94–106, **100**
 - extrinsic contrast parameters, 95–6
 - heat analogy and, 97, **98–9**
 - PD weighting, 96, **99**
 - residual transverse magnetization, 102
 - steady state, 100–1, **101**, 102, 106
 - T1 weighting, 95–6, **96**
 - T2* weighting, 96, **97**
- white matter
 - ADC values, **53**
 - FLAIR imaging of, 85
 - T1 and T2 relaxation times and signal intensity of, **101**
 - T2 decay times of, **29**
 - T1 recovery times of, **26**
- x gradient, 134, 136, 142, 147, 150, 331
- x–y-axis, 14
- y gradient, 134, 136, 142, 147, 331
- z-axis, 7
- Zeeman interaction, 7–8
- z gradient, 134, 136, 141–2, 145, 331
- z gradient amplifier, 331
- zipper artifact, 275–6
 - phase mismapping, 275, **276**
 - causes, 276
 - remedy for, 276

