

Index

a

absorption coefficient 6–7, 9, 10, 13, 115, 310
 acids, PEDOT:PSS 204
 additives, PEDOT:PSS 203
 Ag grid/PEDOT:PSS 208
 Ag nanowires (NW)
 PEDOT:PSS 210–212
 successive multistep growth 109
 synthesis of 108–110
 TCF
 adhesiveness 123–124
 color 119–120
 fabrication of 110–112
 haze factor 117–119
 pattern 112–114
 roughness 121–123
 scanning electron microscopy 119
 stability 124–126
 transparency and conductivity 115–117
 uniformity 120–121
 α CD-containing polyacrylamide (α CD-PAAm) 197
 Al:ZnO (AZO) 94
 angle-resolved photoemission spectroscopy (ARPES) 16
 annular dark-field scanning transmission electron microscopy (ADF-STEM) 170, 172
 anode
 buffer layer 308–309
 transparent electrode 303–304

aqueous solutions 82
 CBD 81–82
 SnO₂ 90–92
 ZnO 88
 arc-discharge method 155–156
 armchair carbon nanotube 143, 147, 148

b

 bandgap renormalization (BGR) 41
 bis(ethylenedioxy)tetrathiafulvalene (BEDO-TTF) 199
 Born-von Kármán periodic boundary conditions 147
 Brillouin zone (BZ)
 graphene 146
 graphene sheet 139
 nanotube 146, 147
 buffer layer
 anode 308–309
 cathode 310
 Burstein–Moss shift (BMS) 34, 41, 51
 B:ZnO (BZO) 94

c

cadmium oxide (CdO) 17, 34, 35, 82, 93
 camphorsulfonic acid (CSA) 196, 197
 carbon-based composites
 applications 216–217
 carbon nanotubes 213–215
 graphene 215–216
 graphene oxide 215–216
 carbon nanotubes (CNT) 25, 213
 arc-discharge method 155

- carbon nanotubes (CNT) (*contd.*)
 - carbon atoms 136
 - chemical vapour deposition 156
 - components of 135
 - electronic properties of 146–151
 - graphene 137–142
 - laser ablation 156
 - mechanical properties 151–152
 - structure of 142–146
 - thermal properties 152–155
 - cathode
 - buffer layer 310
 - transparent electrode 309–310
 - chemical bath deposition (CBD)
 - CdO 93
 - definition of 81–82
 - low temperature post-deposition treatment 93–94
 - In₂O₃ 92
 - principles of 81
 - SnO₂ 90–92
 - TCO devices 94–96
 - ZnO 82–90
 - chemical vapour deposition (CVD) 20, 94, 156
 - graphene 174
 - GTCs 170–171
 - colloidal method 347–348
 - complementary metal oxide semiconductors (CMOS) 176
 - composite films 122, 197–199, 210–213, 215
 - conducting polymeric material 4
 - conductive metal oxides 34, 82
 - conductive polymer 4, 18, 193, 199, 203, 216, 304
 - crystallographic structure
 - ITO 38–42
 - SnO₂ 47–50
 - TiO₂ 50–56
 - ZnO 42–47
 - crystal structure 43, 49, 51, 55, 92, 136, 273, 317, 319, 324
 - cubic close-packed lattice (ccp) 319
 - Cu nanowires (CuNWs) 105, 107, 108, 110, 124, 125, 212
 - Cu(In,Ga)Se₂ (CIGS) 94–96
 - 4-*n*-pentyl-4'-cyanobiphenyl (5CB) 342, 343
- d**
- density-functional calculations (DFT) 33, 39, 44, 49
 - density of states (DOS) 9, 16, 44, 141, 149, 150, 175, 322
 - dibutyl phthalate (DBP) 123
 - dielectric/metal/dielectric (DMD) 304–306
 - dimethylformamide (DMF) 204
 - 1,3-dimethyl-2-imidazolidinone (DMI) 204
 - dimethyl sulfoxide (DMSO) 196, 203, 204, 208, 210, 211, 215
 - Dirac point graphene 167
 - dodecylbenzene sulfonic acid (DBSA)-doped PANI 197
 - Drude–Boltzmann transport theory 8
 - dye sensitized solar cells (DSSCs) 180, 181, 217, 317, 326–331
 - dye molecular composition 327
 - electronic process 326
 - molecule dyes in 328
 - titanium dioxide
 - chemical modification 324–326
 - doping 324
 - electronic considerations 320–321
 - immobilize sensitizer molecules 326–329
 - optical features 322–323
 - photoelectrochemical cells 329–331
 - polymorphs of 317
 - structural properties 319–320
- e**
- electrical contacts
 - circular shape measuring sample 249–250
 - square shape measuring sample 250–252
 - electrical parameters, SnO₂ 48
 - electrical properties

- inhomogeneity 255, 257
- ITO 38–42
- TiO₂ 50–56
- van der Pauw method 248
- ZnO 42–47
- electrochemical polymerization 201–202
- electrochromic (EC) foil
 - color–bleach dynamics 278
 - construction of 275, 276
 - ITO nanoparticles 280
 - mid-luminous transmittance 276, 278
 - PEI–LiTFSI 279
 - roll-to-roll web coating 281
 - spectral transmittance 276, 277
- electrochromic oxide-based materials
 - characterization of 267–268
 - EC foil
 - color–bleach dynamics 278
 - ITO nanoparticles 280
 - mid-luminous transmittance 276, 278
 - PEI–LiTFSI 279
 - principle construction of 275, 276
 - roll-to-roll web coating 281
 - spectral transmittance 276, 277
 - functional principles 268–270
 - nanostructure 270–272
 - optical properties 272–275
 - thin films 282–285
- electrode interface 311–312
- electroless deposition 81, 92, 108
- electroluminescence 301
- electronic properties, CN 146–151
- electronic transport parameters 7–9
- electron mobility 8, 24, 34, 45, 59, 60, 63, 67
- electron paramagnetic resonance (EPR) 322–323
- electrooptical parameters 345, 346
- energy-dispersive X-ray spectroscopy 11
- energy-efficient glazing 266
- ethylene propylene diene monomer (EPDM) 216
- extended X-ray absorption fine structure (EXAFS) 13–15
- f**
 - face centered cubic lattice 137
 - Fermi level 9, 16, 22, 23, 44, 60, 146, 148, 149, 151, 175, 180
 - figure of merit (FoM) 9
 - electrooptical parameters 345–346
 - metal nanowire 115
 - optical, electrical values 219
 - transparent conductive polymers 194
 - finite-element-method (FEM) 251, 252, 254–256, 260
 - Fourier transform IR (FTIR) 12
 - functionalization of reduced graphene oxide (f-rGO) 216
- g**
 - gallium arsenide (GaAs) 180, 182, 252
 - galvanostatic rejuvenation 284, 285
 - gate field-effect transistors (GFETs) 178, 180
 - gel-glass-dispersed liquid crystals (GDLC) 342
 - preparation of 354
 - sol-gel materials 353–355
 - sol-gel technique 352–353
 - 3-glycidoxypropyltrimethoxysilane (GPTMS) 197
 - grain boundaries (GBs) 34, 35, 45, 59, 60, 64, 65, 93, 170, 273
 - graphene (G)
 - Ag nanoparticles 23
 - Brillouin zone 147
 - carbon-based composites 215–216
 - carbon nanotubes 138
 - CVD 20
 - Dirac point 167
 - doped graphene 21
 - engineering work function 175–176
 - GO 19–21
 - metal atoms 22
 - n-type (p-type) 22
 - PVD 23

- graphene (G) (*contd.*)
 TCOs 165
 2D carbon material 165
 2D layer 143
 graphene-based hybrid layers 21
 graphene oxide (GO) 12, 19–21, 23,
 123, 124, 170, 213–216
 graphene–rubber hybrid electrode 216
 graphene transparent conductors
 (GTCs)
 advantages 166
 applications
 photodetectors 178–180
 photovoltaics 180–182
 characterization of 174–175
 heterostructures 175–178
 intrinsic, physical properties
 167–169
 synthesis
 chemical vapor deposition
 170–171
 direct growth 171–173
 graphene solution 169–170
 gray-scale transmittance function 345
 grazing incidence spraying (GIS) 113
- h**
 Hall coefficient 8, 9, 250, 259
 Hall effect
 measuring samples 248
 relative measurement errors 250
 resistances 248
 weighting function 254
 ZnO 259–260
 hexagonal close-packed lattice (hcp)
 319
 hexamethylenetetramine (HMTA) 83,
 92
 highest occupied molecular orbital
 (HOMO) 6, 16, 303
- i**
 indium oxide (In_2O_3) 92
 crystallographic structure 38–39
 electrical parameters 41
 electrical properties 39–40
 optical properties 40–42
 indium-tin-oxide (ITO)
 anode 303–304
 electrical values of 195
 TCO 35
 indium-zinc-oxide (IZO) 38, 303, 304,
 310
 infrared spectroscopy 11–12
 inhomogeneity
 semiconductor electrical property
 254
 ZnO 259–260
 inorganic transparent electrodes 3
 $\text{In}_2\text{O}_3:\text{Sn}$ (ITO) 3
 in-situ polymerization 200–201
 intensity-modulated photocurrent
 spectroscopy (IMPS) 326
 intrinsic zinc oxide (i-ZnO) layer 94
 ionized impurity scattering 33, 44, 45,
 59, 60
- l**
 laser ablation 155, 156
 light-shutter devices based LC 342
 liquid crystal (LC)
 coda 356
 elastic distortion 340
 electrooptical parameters 345–346
 GDLC
 sol-gel materials 353–355
 sol-gel technique 352–353
 indium tin oxide 342
 lyotropic 338, 339
 mesophase 338
 microscopic capsules 355
 molecule 339
 4-*n*-pentyl-4'-cyanobiphenyl 342
 optical anisotropy 342
 PDLC
 colloidal method 347–348
 E7 component 346
 PIPS 348–351
 SIPS 348
 TIPS 348
 polymer-stabilized liquid crystals
 351

- smart-window devices 342–344
 - surface anchoring 341
 - thermotropic 338
 - liquid crystal displays (LCDs) 3, 34, 302, 312
 - liquid phase deposition (LPD) 81, 91, 92
 - lowest unoccupied molecular orbital (LUMO) 6, 309, 311
 - lyotropic liquid crystals 338, 339
- m**
- magnetic flux density 248
 - metal nanowires 18
 - OLED 107
 - synthesis of 105–108
 - TCF
 - adhesiveness 123–124
 - color 119–120
 - fabrication of 110–112
 - haze factor 117–119
 - pattern 112–114
 - roughness 121–123
 - scanning electron microscopy 119
 - stability 124–126
 - transparency and conductivity 115–117
 - uniformity 120–121
 - metal-organic chemical vapour
 - deposition (MOCVD) 34, 61
 - metal-polypyridine complexes 327
 - metal-to-ligand charge transfer (MLCT) 325
 - molecular-beam epitaxy (MBE) 34, 57, 61
 - molecular orbital energy diagram 321
 - multi wall carbon nanotubes (MWCNTs)
 - carbon nanotubes 213–215
 - electronic properties 149
 - nanotubes 142–146
 - thermal properties 150, 151
- n**
- nanoscale grid pattern 18
- N-methyl-4-(4'-formylstyryl) pyridinium methosulfate acetal 113
 - n-type semiconductor 39, 44, 255, 259, 303
- o**
- optical density (OD) 7, 112, 113
 - optical properties
 - characterization of 267–268
 - electrochromic oxide-based materials 272–275
 - ITO 40–42
 - SnO₂ 48
 - TiO₂ 55–56
 - ZnO 46–47
 - organic electroluminescent device 301
 - organic-inorganic hybrid materials 352, 354
 - organic light-emitting diodes (OLEDs) 94, 107, 217, 301
 - anode 303–304
 - buffer layer, anode 308–309
 - cathode 309–311
 - conductive polymer 304
 - DMD 304–307
 - liquid crystal display 302
 - organic/electrode interface 311–312
 - structure of 302
 - transparent electrode 312–314
 - organic-metal-organic (OMO) 17, 209
 - organic photovoltaics (OPVs) 3, 180
 - overcoating layer (OCL) 113, 124, 212
 - oxidative chemical vapor deposition (o-CVD) 200, 201
 - oxidative polymerization 200
 - oxide electrodes-amorphous films 17–18
 - oxide semiconductor 308
- p**
- PANI-poly(2-acrylamido-2-methyl-1-propanesulfonic acid) 197
 - photodetectors 167, 175, 177–180
 - photoelectric effect 15
 - photoelectrochemical cells 317, 329–331

- photoelectrochemical device,
 water-splitting reaction 330
- photoelectrolytic device, water oxidation
 reaction 330
- photoluminescence (PL) 259
- photovoltaics 3, 5, 17, 165, 180–182
- physical vapor deposition (PVD) 19,
 23, 303, 318
- plasma-assisted deposition method 34
- point of zero charge (PZC) 87
- polyaniline (PANI) 194, 196–197, 304
- polycarbazole (PCz) 199
- polycrystalline film 34, 35, 44, 45, 59,
 63, 65, 67
- poly(diallyldimethylammonium
 chloride) (PDDA) 124
- polydimethylsiloxane (PDMS) 123
- poly(4,4-dioctylcyclopentadithiophene)
 199
- polyelectrolyte complexes (PEC) 202
- poly(3,4-ethylenedioxythiophene)
 (PEDOT) 200, 326
- poly(3,4-ethylenedioxythiophene):
 polystyrenesulfonate
 (PEDOT:PSS) 4, 19, 118, 304
- acids 204
- Ag grid 208–210
- AgNW 210–212
- electrical characteristics 205
- formulations 203
- hole injection layer 308
- PEDOT:pTS 207
- salts, ionic liquids, zwitterions
 204–207
- solvents and additives 203–204
- polyethyleneimine-lithium
 bis(trifluoromethylsulfonyl)
 (PEI-LiTFSI) 279
- polyethylene naphthalate (PEN) 17,
 123, 126, 199, 205
- polyethylene terephthalate (PET) 11,
 112, 195, 268
- polyethylenimine ethoxylated (PEIE)
 310
- polymer-dispersed liquid crystal (PDLC)
 colloidal method 347–348
- LC dispersion device 342–344
- PIPS 348–351
- SIPS 348
- TIPS 348
- ultraviolet damage 350
- polymeric liquid crystal devices (PLCD)
 217
- polymerization-induced phase
 separation (PIPS) 348–351
- polymer-metal composites
 Ag grid/PEDOT:PSS 208–210
- AgNW/PEDOT:PSS 210–212
- film composites 212
- polymer-stabilized liquid crystals
 (PSLC) 343, 351
- poly(methylmethacrylate) (PMMA)
 123, 196, 197
- polypyrrole (PPy) 194, 198, 304, 342
- polypyrrole-poly(vinyl alcohol)
 (PPy-PVA) 198
- poly(p-styrene sulfonate-co-acrylic acid
 sodium) (PSA) 208
- poly(styrenesulfonic acid) (PSS) 202
- polythiophene (PTh), thin films 199
- poly(*N*-vinylcarbazole) (PVK)/Ag/PVK
 (PAP) 209
- polyvinylpyrrolidone (PVP) 18, 106,
 197
- p*-toluene sulfonate (PEDOT:*p*TS) 207
- PVK/Ag/PEDOT:PSS (PAPE) 209
- r**
- Raman defects peak 12
- Raman spectroscopy 12, 173
- reduced graphene oxide (rGO-NH₃⁺)
 12, 20, 25, 123, 170, 213, 216
- s**
- sbq-PVA 113
- scanning electron microscopy (SEM)
 119, 170
- Schottky barrier 311, 312
- Schottky emission 309, 311
- self-assembled monolayers (SAM) 92
- sheet density, carriers 8

- sheet resistance (R_s) 3, 7, 8, 10, 17, 18, 20, 22, 23, 95, 105–107, 115, 117, 120–123, 174, 194, 195, 197, 208–213, 215, 216, 219
- silver nanowires (Ag NWs) 18, 219, 342
- single-layer graphene (SLG) 22, 167, 216
- single wall carbon nanotubes (SWNTs) 213–215
 nanotubes 142–151
 thermal properties 152–155
- smart-window devices 337, 342–344
 GDLC 356
- sodium citrate tribasic (SDA) 88
- sodium dodecylbenzenesulfonate (SDBS) 215
- solar irradiance spectrum 267, 268
- sol-gel materials 353–355
- sol-gel technique 318, 352, 354
- solvent induced phase separation (SIPS) 348
- solvents, PEDOT:PSS 203
- spectroscopy
 Raman and infrared 11–12
 UPS 15–17
 XAS 13–15
 XPS 15–17
- stannous oxide (SnO) 48, 91
- stoichiometric titanium oxides 53
- stoichiometric zinc oxide 44
- structure directing agents (SDA) 83, 85, 86
- successive multistep growth (SMG) 109
- sulfonated carbon nanotubes (SCNT) 213
- sulfonated graphene (S-Gra) 216
- surface enhanced Raman spectroscopy (SERS) 183
- synchrotron radiation, XAS 13
- t**
- tetragonal anatase crystal 52
- tetrathiafulvalene (TTF)-tethered polymers 199
- thermal conductivity 137, 153–155
- thermally-induced phase separation (TIPS) 348
- thermal properties
 carbon nanotubes 152
 mechanical 151–152
- thermal roll imprinting (TRI) 208
- thin films
 electrochromic 282–285
 properties
 ITO 57–59
 SnO₂ 60–63
 TiO₂ 63–67
 ZnO 59–60
- thiol-ene photopolymerization 350
- thiol-ene polymerization 349
- Timoshenko beam theory 152
- tin-doped indium oxide (ITO)
 crystallographic structure 38–39
 electrical properties 39–40
 optical properties 40–42
 thin film 57–67
- tin oxide (SnO₂) 90
 crystallographic structure 48
 electrical parameters 48
 molecular orbital energy diagram 321
 optical properties 48–50
 TCO 35
 thin film 60–63
- titanium dioxide (TiO₂)
 chemical modification 324–326
 crystallographic structure 50–53
 DSSC 317
 electrical properties 53–55
 electronic considerations 320–321
 immobilize sensitizer molecules 326–329
 optical features 322–323
 optical properties 55–56
 organometallic dyes 324–326
 photoelectrochemical cells 329–331
 structural properties 319–320
 thin film 63–67
- topological insulators (TIs) 4

- transmittance 5–7, 9, 10, 18, 20, 33, 40, 41, 46, 47, 50, 56, 92, 93, 96, 165, 166, 168, 169, 174, 195–201, 207–209, 213, 215, 216, 275, 276, 278, 279, 281, 283, 285
 - transparent conducting films
 - doped graphene 21–24
 - graphene and GO 19–21
 - metallic nanowires, grids 18–19
 - oxide electrodes-amorphous films 17–18
 - transmittance 6–7
 - transparent conducting oxides (TCO)
 - CNT 24
 - oxide electrodes-amorphous films 17–18
 - spectroscopy 13–15
 - transparent conductive films (TCF) 7
 - AgNWs 106, 107
 - metal nanowires
 - adhesiveness 123–124
 - color 119–120
 - fabrication of 110–112
 - haze factor 117–119
 - pattern 112–114
 - roughness 121–123
 - stability 124–126
 - transparency and conductivity 115–117
 - uniformity 120–121
 - transparent conductive oxides (TCO) 4
 - CBD 89
 - electron orbitals and effective masses 36
 - ITO
 - crystallographic structure 38–39
 - electrical properties 39–40
 - optical properties 40–42
 - thin film 57–67
 - material class of 33, 35
 - of silicon 36
 - SnO₂
 - crystallographic structure 48
 - electrical parameters 48
 - optical parameters 48–50
 - thin film 60–63
 - TiO₂
 - crystallographic structure 50–53
 - electrical properties 53–55
 - optical properties 55–56
 - thin film 63–67
 - ZnO
 - crystallographic structure 43–44
 - electrical properties 44–46
 - optical properties 46–47
 - thin film 59–60
 - transparent conductive polymers
 - carbon-based composites
 - applications 216–217
 - carbon nanotubes 213–215
 - figure of merit 194–195
 - PEDOT:PSS 202–208
 - polyaniline 196–197
 - polymer-metal composites
 - Ag grid/PEDOT:PSS 208–209
 - AgNW/PEDOT:PSS 210–212
 - film composites 212
 - poly(3,4-ethylenedioxythiophene)
 - PEDOT 200–302
 - polypyrrole 198
 - transparent electrodes 3
 - absorption coefficient 6–7
 - anode 303–304
 - buffer layer 308–309
 - cathode 309–310
 - conductive polymer 304
 - DMD 304–307
 - electronic transport parameters 7–9
 - figure of merit 9–11
 - nanowire networks 11
 - OLEDs 312–314
 - organic/electrode interface 311–312
 - TCO 34
 - transmittance 5–6
 - transparent film 3, 4, 212, 216
 - trimethylamine borane (TMBA) 92
- u**
- ultraviolet light-emitting diodes (UV-LEDs) 213

ultraviolet photoelectron spectroscopy (UPS) 15
 urban heat islands 266

V

valence band 4, 6, 16, 33, 44, 53, 140, 180, 301, 302, 321, 322
 valence band maxima (VBM) 48
 van der Pauw method 6, 7, 247
 electrical contacts
 circular shape measuring sample 249–250
 square shape measuring sample 250–252
 electrical property measurement 248
 finite-element-method 251
 inhomogeneity
 semiconductor electrical property 254
 ZnO 259–260
 van der Waals (vdW), heterojunction interface 176
 vapor phase polymerization (VPP) 200, 201

W

water-splitting reaction 329, 330
 weighting functions 254
 wide-bandgap semiconductors 67, 165, 253, 268
 Wigner-Seitz cell 139

work function, electronic 16
 wurtzite crystal structure 43

X

X-ray absorption near edge structure (XANES) 15
 X-ray absorption spectroscopy (XAS)
 experiments 13
 K-edge Mo XANES 14
 K-edge Ti XANES 15
 synchrotron radiation 13
 X-ray photoelectron spectroscopy (XPS)
 and UPS 15

Z

Zinc oxide (ZnO)
 Al:ZnO 88
 ammonia 83
 aqueous solutions 88
 crystallographic structure 43–44
 crystals 85
 doping 87
 electrical properties 44–46
 Ga:ZnO 90
 hexamethylenetetraamine 83
 methoxyethanol 86
 optical properties 46–47
 point of zero charge 87
 structure directing agent 87
 TCO 35
 thin film 59–60
 zinc ammine based 84

